



Mine Safety Appliances Company • Instrument Division • P.O. Box 427 • Pittsburgh, PA 15230-0427

Telephone: (800) MSA-INST

August 25, 2000

To whom it may concern:

MSA P/N 486679, the battery pack used in the MSA Model 360[®], MSA Model 361[®], Combustible Gas monitors is considered an article as defined in 29CFR 1910.1200 (c). Articles are exempt from the Hazard Communication Standard and no MSDS is required for this product. In order to aid in your understanding the contents of this battery pack the following table lists potential hazardous components within the battery pack at the time of manufacture.

POTENTIAL HAZARDOUS COMPONENTS	% (By weight)
Lead (CAS 7439-92-1)	45-60%
Lead dioxide(CAS 1309-60-0)	15-20%
Sulfuric Acid Electrolyte(CAS 7664-93-9)	15-20%
Non-Hazardous Materials	5-10%

The state of charge of the battery as well as the environment in which you used the battery pack may have impacted its contents. It is your responsibility to dispose of spent battery packs in accordance with local, state, and federal laws and regulations. Please provide this information to your regulatory affairs and/or safety officer. Batteries may be shipped to a reclamation facility for recovery of the metal and plastic components.

DOT classification “ nonspillable batteries”

Should you have additional questions contact MSA at the above phone number.