



Mine Safety Appliances Company • Cranberry Plant • P.O. Box 427 • Pittsburgh, PA 15230-0427

Telephone: (724) 776-8600

To whom it may concern:

MSA P/N 655759, the battery used in the TOXGUARD II ® gas monitor and is considered an article as defined in 29 CFR 1910.1200 (c). Articles are exempt from the Hazard Communication Standard and no MSDS is required for this product. In order to aid in your understanding the contents of this battery the following table lists potential hazardous components within the battery pack at the time of manufacture.

CHEMICAL COMPONENTS	QUANTITY % wt.
Lead	48-53%
Lead Oxide	23-26%
Lead Sulfate	< 1%
Sulfuric Acid	7-10%

The state of charge of the battery as well as the environment in which you used the battery pack may have impacted its contents. It is your responsibility to dispose of spent battery packs in accordance with local, state, and federal laws and regulations. Please provide this information to your regulatory affairs and/or safety officer.

Should you have additional questions contact MSA at the above telephone number.

Creation Date – March 10, 2005

Revision 1: Nov 4, 2008