

MSA Corporate Center

1000 Cranberry Woods Drive Cranberry Township, PA 16066 800.MSA.2222 www.MSAsafety.com

Telephone: 724-776-8600

To whom it may concern:

MSA P/N A-ULTX-SENS-32-0-X is sensor used for monitoring of combustible gas concentrations using an Ultima® X Series gas monitor and is considered to be an article as defined in 29 CFR 1910.1200 (c). Articles are exempt from the Hazard Communication Standard; therefore no MSDS is required for this product. In order to aid in your understanding of the sensor contents, the following table lists chemical components within the sensor at the time of manufacture.

POTENTIAL HAZARDOUS COMPONENTS	QUANTITY
Lead solder encapsulated in epoxy	≤ 5 grams
(all or part of the lead may be in the form of lead oxide)	

Please note that environments in which this sensor was exposed during use or otherwise may have impacted its contents and that it is the users, responsibility to dispose of the sensor in accordance with local, state, and federal laws and regulations. Please provide this information to your regulatory affairs and/or safety officer.

Should you have additional questions please contact MSA at the above phone number.

Creation Date: February 18, 2013

.

Revision 0: February 2013