
HEALTH HAZARDS

HEALTH HAZARDS- Before adverse health effects or suffocation could occur the LEL of Propane in air may be exceeded possibly causing an explosive atmosphere as well as an oxygen deficient environment. Due to the small size of the individual cylinder of this product no health effects to the product are anticipated under routine circumstances of use. The most significant hazard associated with this gas mixture when it contains less than 19.5% oxygen is the potential for exposure to oxygen deficient atmospheres.

SIGNS AND SYMPTOMS OF EXPOSURE - Individuals in an oxygen deficient environment may experience headaches, ringing in the ears, dizziness, drowsiness, unconsciousness nausea, vomiting and depression of all the senses.

PRIMARY ROUTES OF ENTRY – Inhalation.

TARGET ORGANS – Respiratory system, eyes, hear, cardiovascular system, and CNS.

MEDICAL CONDITIONS GENERALLY RECOGNIZED AS BEING AGGRAVATED BY EXPOSURE – Acute or chronic respiratory conditions may be aggravated by overexposure to the contents of this cylinder.

EXPOSURE LIMITS – (ACGIH 2005) Propane(as an alkane)1000 ppm. Nitrogen None

CARCINOGENICITY DATA - NIOSH RTECS, OSHA, NTP or IARC does not list component gases.

EMERGENCY AND FIRST AID PROCEDURES - Remove from exposure

SAFE HANDLING AND USE

HYGIENIC PRACTICES - Avoid breathing gas.

PROTECTIVE MEASURES DURING REPAIR AND MAINTENANCE OF CONTAMINATED EQUIPMENT - N/A

PROCEDURES FOR SPILL OR LEAK CLEANUP - Ventilate Area. Avoid breathing gas.

WASTE DISPOSAL - Do not puncture or incinerate cylinder. Before discarding cylinder, slowly release contents to a safe exhaust. Dispose of cylinder in accordance with local, state and federal regulations

STORAGE - Store in a cool, dry, well-ventilated area. Do not exceed 120°F.

CONTROL MEASURES

PERSONAL PROTECTIVE EQUIPMENT - Due to the limited amount of gas in the cylinder, and the low release rate employed in instrument calibration, respiratory protection is not indicated under conditions of intended use.

ENGINEERING CONTROLS - Mechanical ventilation is suitable.

WORK PRACTICES - Avoid breathing gas. Use in well-ventilated areas. Follow the calibration procedure detailed in the MSA instruction manual provided with the instrument under calibration.

DATE OF PREPARATION - Rev. 0, July 2006

WARNING: This is a hazardous chemical product. By following the directions and warnings provided with this product, the hazards associated with the use of this product can be greatly reduced but never entirely eliminated. Mine Safety Appliances Company makes no warranties, expressed or implied, with respect to this product and EXPRESSLY DISCLAIMS THE WARRANTY OF MERCHANTABILITY AND ANY WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. Users assume all risks in handling, using or storing this product.