

This product contains methane, carbon monoxide, oxygen and nitrogen, substances subject to the Pennsylvania Worker and Community Right-To-Know Act.

---

**PRODUCT IDENTITY**

---

LABEL IDENTITY - MSA P/N 710566 Calibration Check Gas, 2.5% Methane, 60 ppm Carbon Monoxide, 15% Oxygen, Balance Nitrogen

CHEMICAL NAME - Methane, Carbon Monoxide, Oxygen, Nitrogen Mixture

ADDITIONAL IDENTITIES - MSA P/N 710566 Calibration Gas

FORMULA -  $CH_4 + CO + O_2 + N_2$

---

**APPLICABLE CHEMICAL CONTENTS**

---

	<u>%</u>	<u>TWA</u>
Methane (CAS 74-82-8)	2.5	1000 ppm*
Carbon Monoxide (CAS 630-08-0) (ACGIH 2009)	0.0060	25 ppm
Oxygen (CAS 7782-44-7)	15	None
Nitrogen (CAS 7727-37-9)	Balance	None

\*Methane as an alkane (ACGIH 2009)

NOTE: Gas under pressure, 2200 PSIG at 70°F, approx. 552 Liters gas at atmospheric pressure

---

**PHYSICAL AND CHEMICAL PROPERTIES**

---

APPEARANCE AND ODOR - Colorless, Odorless Gas  
Following information is for Nitrogen the main component of this gas mixture

BOILING POINT - -320.4°F (-195.8 °C)      SPECIFIC GRAVITY (air = 1) @70°F (21.1 °C): 0.906

VAPOR PRESSURE @70°F (21.1 °C): N/A\*      PERCENT VOLATILE BY VOLUME - N/A\*

GAS DENSITY @32°F (0 °C) and 1 atm: 0.072 lbs/ft<sup>3</sup> (1.153 kg/ m<sup>3</sup>)

SOLUBILITY IN WATER - Methane - 9 cm<sup>3</sup>/100 ml (20°C)  
Carbon Monoxide - 3.5 cm<sup>3</sup>/100 ml (0°C)  
Oxygen - 3.2 cm<sup>3</sup>/100 ml (25°C)  
Nitrogen - 2.3 cm<sup>3</sup>/100 ml (0°C)

\*\*N/A - Not Applicable

---

**PHYSICAL HAZARD INFORMATION**

---

PHYSICAL HAZARD - Compressed Gas, 2200 PSIG at 70°F

CONDITIONS OR MATERIALS TO AVOID - None

FLASH POINT - N/A\*\*      LEL - N/A\*\*      UEL - N/A\*\*

EXTINGUISHING MEDIA - This Gas Mixture is not flammable

SPECIAL FIRE FIGHTING PROCEDURES - See Next Item

UNUSUAL FIRE AND EXPLOSION HAZARDS - Gas under pressure, 2200 PSIG at 70°F. Do not exceed 120°F.

\*\*N/A-Not Applicable

---

**HEALTH HAZARDS**

---

HEALTH HAZARDS - Methane as an alkane 1000 ppm (ACGIH 2009). Carbon monoxide TC<sub>LO</sub> (Human) is reportedly 650 ppm/45 minutes; LCLO (Human) 5000 ppm/5 minutes.

SIGNS AND SYMPTOMS OF EXPOSURE – Methane as an alkane CNS depression, cardiac sensitization. Carbon monoxide exposure to 500-1000 ppm may cause headache, rapid breathing, nausea, weakness, dizziness and confusion.

PRIMARY ROUTES OF ENTRY - Inhalation

TARGET ORGANS – Methane as an alkane heart and CNS. Carbon monoxide: Lungs, Blood, Tissues. Carbon monoxide at toxic concentrations causes tissue hypoxia (lack of oxygen) by preventing blood from transporting sufficient oxygen.

MEDICAL CONDITIONS GENERALLY RECOGNIZED AS BEING AGGRAVATED BY EXPOSURE - Carbon monoxide burden may aggravate angina pectoris. Pregnant women are reportedly more sensitive than others. Effects of Carbon monoxide exposure are aggravated by heavy labor, heat stress and high altitude.

EXPOSURE LIMITS - Carbon monoxide: (ACGIH 2009) TWA 25 ppm . Carbon monoxide (OSHA) TWA=35 ppm

CARCINOGENICITY DATA - NIOSH RTECS, OSHA, NTP or IARC does not list Component gases.

EMERGENCY AND FIRST AID PROCEDURES - Remove from exposure. If breathing has stopped, give artificial respiration. Administer oxygen. Consult a physician immediately

---

**SAFE HANDLING AND USE**

---

HYGIENIC PRACTICES - Avoid breathing gas.

PROTECTIVE MEASURES DURING REPAIR AND MAINTENANCE OF CONTAMINATED EQUIPMENT - N/A\*\*

PROCEDURES FOR SPILL OR LEAK CLEANUP - Ventilate Area.

WASTE DISPOSAL - Do not puncture or incinerate cylinder. Before discarding cylinder, slowly release contents to a safe exhaust. Dispose of cylinder in accordance with local, state and federal regulations.

STORAGE - Store in a cool, dry, well-ventilated area. Do not exceed 120°F.

\*\*N/A-Not Applicable

---

**CONTROL MEASURES**

---

PERSONAL PROTECTIVE EQUIPMENT - Due to the limited amount of gas in the cylinder, and the low release rate employed in instrument calibration, respiratory protection is not indicated under conditions of intended use.

ENGINEERING CONTROLS - Mechanical ventilation is suitable.

WORK PRACTICES - Avoid breathing gas. Use in well-ventilated areas. Follow the calibration procedure detailed in the MSA instruction manual provided with the instrument under calibration.

DATE OF PREPARATION – Rev 5, January 2010

WARNING: This is a hazardous chemical product. By following the directions and warnings provided with this product, the hazards associated with the use of this product can be greatly reduced but never entirely eliminated. Mine Safety Appliances Company makes no warranties, expressed or implied, with respect to this product and EXPRESSLY DISCLAIMS THE WARRANTY OF MERCHANTABILITY AND ANY WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. Users assume all risks in handling, using or storing this product.