

MATERIAL SAFETY DATA SHEET
29 CFR 1910.1200 OSHA Hazard
Communication Rule Format
Chem-Tel 24 Hour Emergency # 1-800-255-3924

MINE SAFETY APPLIANCES COMPANY
P.O. Box 426
Pittsburgh, PA 15230
PHONE (412) 967-3000

This product contains methane, oxygen, hydrogen sulfide and nitrogen, substances subject to the Pennsylvania Worker and Community Right-To-Know Act.

PRODUCT IDENTITY

LABEL IDENTITY - MSA P/N 711056 Calibration Check Gas, 1.45% Methane, 15% Oxygen, 10 ppm Hydrogen Sulfide, Nitrogen Balance

CHEMICAL NAME - Methane, Oxygen, Hydrogen Sulfide, Nitrogen Mixture

ADDITIONAL IDENTITIES - MSA P/N 711056 Calibration Gas

FORMULA - $\text{CH}_4 + \text{O}_2 + \text{H}_2\text{S} + \text{N}_2$

APPLICABLE CHEMICAL CONTENTS

	<u>%</u>	<u>TWA</u>	<u>STEL</u>
Methane (CAS 74-82-8)	1.45	1000 ppm*	
Oxygen (CAS 7782-44-7)	15	None	
Hydrogen Sulfide (CAS 7783-06-4)(ACGIH 2010)	0.0010	1 ppm	5 ppm
Nitrogen (CAS 7727-37-9)	Balance	None	

*Methane as an alkane (ACGIH 2010)

NOTE: Gas Under Pressure, 500 PSIG at 70°F, Approx. 34 Liters Gas at Atmospheric Pressure

PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR - Colorless, Malodorous Gas

Following information is for Nitrogen the main component of this gas mixture

BOILING POINT - -320.4°F (-195.8 ° C) SPECIFIC GRAVITY (air = 1) @70°F (21.1 °C): 0.906

VAPOR PRESSURE @70°F (21.1 °C): N/A* PERCENT VOLATILE BY VOLUME - N/A*

GAS DENSITY @32°F (0 °C) and 1 atm: 0.072 lbs/ft³ (1.153 kg/ m³)

VAPOR DENSITY (AIR = 1) - < 1

SOLUBILITY IN WATER - Methane - 9 cm³/100 ml (20°C)
 Oxygen - 3.2 cm³/100 ml (25°C)
 Hydrogen Sulfide - 437 cm³/100 ml (0°C)
 Nitrogen - 2.3 cm³/100 ml (0°C)

N/A - Not Applicable

PHYSICAL HAZARD INFORMATION

PHYSICAL HAZARD - Compressed Gas, 500 PSIG at 70°F

CONDITIONS OR MATERIALS TO AVOID - None

FLASH POINT - N/A

LEL - N/A

UEL - N/A

EXTINGUISHING MEDIA - This Calibration Gas Mixture is not flammable

SPECIAL FIRE FIGHTING PROCEDURES - See Next Item

UNUSUAL FIRE AND EXPLOSION HAZARDS - Gas Under Pressure, 500 PSIG at 70°F. Do Not Exceed 120°F.

HEALTH HAZARDS

HEALTH HAZARDS –

- Methane as an alkane CNS depression and cardiac sensitization at 1000 ppm.
- Hydrogen Sulfide LC_{LO} 800 ppm/5 minutes. No effects known below 10 ppm.

SIGNS AND SYMPTOMS OF EXPOSURE -

- Methane: Cardiac sensitization and Central nervous system depression at 1000ppm.
- Hydrogen sulfide is an irritant of the eyes and respiratory tract.

PRIMARY ROUTES OF ENTRY - Inhalation, eyes

TARGET ORGANS - Lungs, eyes, respiratory tract

MEDICAL CONDITIONS GENERALLY RECOGNIZED AS BEING AGGRAVATED BY EXPOSURE - No Information

EXPOSURE LIMITS –

- Methane as an alkane 1000 ppm. (ACGIH 2010).
- Hydrogen sulfide TWA 1 ppm, STEL 5 ppm

CARCINOGENICITY DATA - NIOSH RTECS, OSHA, NTP or IARC does not list component gases.

EMERGENCY AND FIRST AID PROCEDURES - Remove from Exposure.

SAFE HANDLING AND USE

HYGIENIC PRACTICES - Avoid Breathing Gas

PROTECTIVE MEASURES DURING REPAIR AND MAINTENANCE OF CONTAMINATED EQUIPMENT - N/A

PROCEDURES FOR SPILL OR LEAK CLEANUP - Ventilate Area. Avoid Breathing Gas.

WASTE DISPOSAL - Do not puncture or incinerate cylinder. Before discarding cylinder, slowly release contents to a safe exhaust.

STORAGE - Store in a cool, dry, well-ventilated area. Do not exceed 120°F.

CONTROL MEASURES

PERSONAL PROTECTIVE EQUIPMENT - Due to the limited amount of gas in the cylinder, and the low release rate employed in instrument calibration, respiratory protection is not indicated under conditions of intended use.

ENGINEERING CONTROLS - Mechanical ventilation is suitable.

WORK PRACTICES - Avoid breathing gas. Use in well-ventilated areas. Follow the calibration procedure detailed in the MSA instruction manual provided with the instrument under calibration.

DATE OF PREPARATION - Rev. 6, October 2010

WARNING: This is a hazardous chemical product. By following the directions and warnings provided with this product, the hazards associated with the use of this product can be greatly reduced but never entirely eliminated. Mine Safety Appliances Company makes no warranties, expressed or implied, with respect to this product and EXPRESSLY DISCLAIMS THE WARRANTY OF MERCHANTABILITY AND ANY WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. Users assume all risks in handling, using or storing this product.