MATERIAL SAFETY DATA SHEET 29 CFR 1910.1200 OSHA Hazard Communication Rule Format Chem-Tel 24 Hour Emergency # 1-800-255-3924

MINE SAFETY APPLIANCES COMPANY P.O. Box 426 Pittsburgh, PA 15230 PHONE (412) 967-3000

This product contains carbon monoxide, propane, oxygen and nitrogen, substances subject to the Pennsylvania Worker and Community Right-To-Know Act.

PRODUCT IDENTITY

LABEL IDENTITY - MSA P/N 801051 Calibration Check Gas, 60 ppm Carbon Monoxide, 0.6% Propane and 15%

Oxygen in Nitrogen

CHEMICAL NAME - Carbon Monoxide, Propane, Oxygen, Nitrogen Mixture

ADDITIONAL IDENTITIES - MSA P/N 801051 calibration Gas

FORMULA - $CO + C_3H_8 + O_2$ in N_2

APPLICABLE CHEMICAL CONTENTS		
	<u>%</u>	<u>TWA</u>
Carbon Monoxide (CAS 630-08-0) (ACGIH 2003)	0.0060	25 ppm
Propane (CAS 74-98-6)	0.6	None*
Oxygen (CAS 7782-44-7)	15	None
Nitrogen	Balance	None
*Propane is a simple asphyxiant		

The same of the sa

NOTE: Gas under pressure, 1000 PSIG at 70°F, ~100 liters at atmospheric pressure.

PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR - Colorless, odorless gas

BOILING POINT - N/A SPECIFIC GRAVITY $(H_2O=1)$ - N/A VAPOR PRESSURE - N/A PERCENT VOLATILE BY VOLUME - N/A

VAPOR DENSITY (AIR = 1) - Approx. 1+

SOLUBILITY IN WATER - Carbon Monoxide - 3.5 cm³/100 ml (0°C)

Propane - 6.5 cm³/100 ml (18°C) Oxygen - 3.2 cm³/100 ml (25°C) Nitrogen - 2.3 cm³/100 ml (0°C)

N/A - Not Applicable

PHYSICAL HAZARD INFORMATION

PHYSICAL HAZARD - Compressed gas, 1000 PSIG at 70°F

CONDITIONS OR MATERIALS TO AVOID - None

FLASH POINT - N/A LEL - N/A UEL - N/A

EXTINGUISHING MEDIA - This calibration gas mixture is not flammable

SPECIAL FIRE FIGHTING PROCEDURES - See next item.

UNUSUAL FIRE AND EXPLOSION HAZARDS - Gas under pressure, 1000 PSIG at 70°F. Do not exceed 120°F.

HEALTH HAZARDS

HEALTH HAZARDS - Propane is a simple asphyxiant (ACGIH 2003). Carbon monoxide TC_{LO} (human) is 650 ppm/45 minutes; LC_{LO} (human) 5000 ppm/5 minutes.

SIGNS AND SYMPTOMS OF EXPOSURE - None known for 0.6% propane. Exposure to 500-1000 ppm carbon monoxide may cause headache, rapid breathing, nausea, weakness, dizziness and confusion.

PRIMARY ROUTES OF ENTRY - Inhalation

TARGET ORGANS - Carbon monoxide: Lungs, blood, and tissues. Carbon monoxide at toxic concentrations causes tissue hypoxia (lack of oxygen) by preventing blood from transporting sufficient oxygen.

MEDICAL CONDITIONS GENERALLY RECOGNIZED AS BEING AGGRAVATED BY EXPOSURE - Carbon Monoxide burden may aggravate angina pectoris. Pregnant women are reportedly more sensitive than others. Effects of Carbon monoxide exposure are aggravated by heavy labor, heat stress and high altitude.

EXPOSURE LIMITS - Carbon Monoxide 25 ppm (ACGIH 2003)

CARCINOGENICITY DATA - NIOSH RTECS, NTP, OSHA or IARC does not list component gases.

EMERGENCY AND FIRST AID PROCEDURES - Remove from exposure. Administer oxygen. Consult physician immediately.

SAFE HANDLING AND USE

HYGIENIC PRACTICES - Avoid breathing gas.

PROTECTIVE MEASURES DURING REPAIR AND MAINTENANCE OF CONTAMINATED EQUIPMENT - N/A

PROCEDURES FOR SPILL OR LEAK CLEANUP - Ventilate area.

WASTE DISPOSAL - Do not puncture or incinerate cylinder. Before discarding cylinder, slowly release contents to a safe exhaust. Dispose of cylinder in accordance with a local, state, and federal regulations.

STORAGE - Store in a cool, dry, well-ventilated area. Do not exceed 120°F.

CONTROL MEASURES

PERSONAL PROTECTIVE EQUIPMENT - Due to the limited amount of gas in the cylinder, and the low release rate employed in instrument calibration, respiratory protection is not indicated under conditions of intended use.

ENGINEERING CONTROLS - Mechanical ventilation is suitable.

WORK PRACTICES - Avoid breathing gas. Use in well-ventilated areas. Follow the calibration procedure detailed in the MSA instruction manual provided with the instrument under calibration.

DATE OF PREPARATION - Rev. 6, October 2003

WARNING: This is a hazardous chemical product. By following the directions and warnings provided with this product, the hazards associated with the use of this product can be greatly reduced but never entirely eliminated. Mine Safety Appliances Company makes no warranties, expressed or implied, with respect to this product and EXPRESSLY DISCLAIMS THE WARRANTY OF MERCHANTABILITY AND ANY WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. Users assume all risks in handling, using or storing this product.