

This product contains nitrogen, a substance subject to the Pennsylvania Worker and Community Right-To-Know Act.

PRODUCT IDENTITY

LABEL IDENTITY - MSA P/N 813370 Calibration Check Gas, 30 ppm R-500 in Nitrogen

CHEMICAL NAME - Mixture of 73.8% of dichlorodifluoromethane(R-12) and 26.2% of difluoroethane(R-152A) in Nitrogen

ADDITIONAL IDENTITIES - MSA P/N 812823 Calibration Gas 30 ppm R-500 in Nitrogen

FORMULA - CCl_2F_2 , CH_3CHF_2 , in N_2

APPLICABLE CHEMICAL CONTENTS

	<u>%</u>	<u>TWA</u>
CCl_2F_2 (CAS 75-71-8)	0.00221	1000 ppm
CH_3CHF_2 (CAS 75-37-6)	0.00079	None established
Nitrogen (CAS 7727-37-9)	Balance	None

NOTE: Gas Under Pressure, 1000 PSIG at 70°F, Approx. 100 Liters Gas at Atmospheric Pressure

PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR - Colorless, Odorless Gas Mixture

BOILING POINT - N/A

VAPOR PRESSURE - N/A

VAPOR DENSITY (AIR = 1) - > 1

SOLUBILITY IN WATER - CCl_2F_2 - approx. 6 cm³/100 ml (25°C)
 CH_3CHF_2 - approx. 0.12 cm³/100 ml (25°C)
Nitrogen - 2.3 cm³/100 ml (0°C)

SPECIFIC GRAVITY (H₂O = 1) - N/A

PERCENT VOLATILE BY VOLUME - N/A

N/A - Not Applicable

PHYSICAL HAZARD INFORMATION

PHYSICAL HAZARD - Compressed Gas, 1000 PSIG at 70°F

CONDITIONS OR MATERIALS TO AVOID - Avoid bases. Avoid powdered active metals such as aluminum, alkali metals or alkaline earth metals.

FLASH POINT - N/A

LEL - N/A

UEL - N/A

EXTINGUISHING MEDIA - This Calibration Gas Mixture Is Not Flammable

SPECIAL FIRE FIGHTING PROCEDURES - CCl_2F_2 decomposes at high temperatures yielding toxic halogen compounds. Thermal decomposition or burning of the CH_3CHF_2 may produce toxic fumes of fluorides/CO/CO₂. Use self-contained pressure demand type breathing apparatus with full facepiece.

UNUSUAL FIRE AND EXPLOSION HAZARDS - Gas Under Pressure, 1000 PSIG at 70°F. Do Not Exceed 120°F.

HEALTH HAZARDS

HEALTH HAZARDS - The ACGIH TWA for R-12 is 1000 ppm. R-12 inhalation 30 minute LC50 (RAT) is 800,000 ppm. The ACGIH TWA for R-152A is not currently established. R-152A inhalation 4 hour ALC (RAT) is 383,000 ppm. Nitrogen is an asphyxiant.

SIGNS AND SYMPTOMS OF EXPOSURE: None known for 30 ppm R-500. Nitrogen is an asphyxiant. Significant dilution of ambient air by asphyxiant causes air hunger, increased breathing frequency, drowsiness, weakness, and ringing in ears.

PRIMARY ROUTES OF ENTRY - Inhalation

TARGET ORGANS - Lungs

MEDICAL CONDITIONS GENERALLY RECOGNIZED AS BEING AGGRAVATED BY EXPOSURE - No Information

EXPOSURE LIMITS - ACGIH TWA for R-12 is 1000 ppm. ACGIH TWA for R-152A is not currently established

CARCINOGENICITY DATA - Neither nitrogen, R-12, nor R-152A is listed by NIOSH, RTECS, IARC, NTP or OSHA.

EMERGENCY AND FIRST AID PROCEDURES - Remove victim from exposure. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

SAFE HANDLING AND USE

HYGIENIC PRACTICES - Avoid Breathing Gas

PROTECTIVE MEASURES DURING REPAIR AND MAINTENANCE OF CONTAMINATED EQUIPMENT - N/A

PROCEDURES FOR SPILL OR LEAK CLEANUP - Ventilate Area

WASTE DISPOSAL - Do not puncture or incinerate cylinder. Before discarding cylinder, slowly release contents to a safe exhaust.

STORAGE - Store in a cool, dry, well-ventilated area. Do not exceed 120°F.

CONTROL MEASURES

PERSONAL PROTECTIVE EQUIPMENT - Due to the limited amount of gas in the cylinder, and the low release rate employed in instrument calibration, respiratory protection is not indicated under conditions of intended use.

ENGINEERING CONTROLS - Mechanical ventilation is suitable.

WORK PRACTICES - Avoid breathing gas. Use in well-ventilated areas. Follow the calibration procedure detailed in the MSA instruction manual provided with the instrument under calibration.

DATE OF PREPARATION - Rev. 3, June 1999

WARNING: This is a hazardous chemical product. By following the directions and warnings provided with this product, the hazards associated with the use of this product can be greatly reduced but never entirely eliminated. Mine Safety Appliances Company makes no warranties, expressed or implied, with respect to this product and EXPRESSLY DISCLAIMS THE WARRANTY OF MERCHANTABILITY AND ANY WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. Users assume all risks in handling, using or storing this product.