
HEALTH HAZARDS

HEALTH HAZARDS - Hydrogen chloride is extremely irritating the airway, eyes, and skin. It is toxic and corrosive.

LC_{LO} Human 3000 ppm/5minutes

LC₅₀ Rat 3124 ppm/30minutes

LC₅₀ Mouse 1108 ppm/1 hour

SIGNS AND SYMPTOMS OF EXPOSURE -Symptoms of exposure may include burning sensations, coughing, wheezing, laryngitis, shortness of breath, headache, nausea, and vomiting.

PRIMARY ROUTES OF ENTRY - Inhalation, eyes

TARGET ORGANS - Respiratory tract, eyes, skin.

MEDICAL CONDITIONS GENERALLY RECOGNIZED AS BEING AGGRAVATED BY EXPOSURE - No Information

EXPOSURE LIMITS - ACGIH 2011: Hydrogen Chloride 2 ppm ceiling.

CARCINOGENICITY DATA - NIOSH RTECS, OSHA, NTP or IARC does not list component gases.

EMERGENCY AND FIRST AID PROCEDURES -

Eyes: Immediately wash the eyes with large amounts of water, occasionally lifting the lower and upper lids. Get medical attention immediately.

Skin: Immediately flush the contaminated skin with water. Get medical attention promptly.

Breath: Remove from exposure. If breathing has stopped, give artificial respiration. Get medical attention as soon as possible.

SAFE HANDLING AND USE

HYGIENIC PRACTICES - Avoid breathing gas.

PROTECTIVE MEASURES DURING REPAIR AND MAINTENANCE OF CONTAMINATED EQUIPMENT - N/A

PROCEDURES FOR SPILL OR LEAK CLEANUP - Ventilate area.

WASTE DISPOSAL - Do not puncture or incinerate cylinder. Before discarding cylinder, slowly release contents to a safe exhaust. Dispose of cylinder in accordance with local, state, and federal regulations.

STORAGE - Store in a cool, dry, well-ventilated area. Do not exceed 120°F.

CONTROL MEASURES

PERSONAL PROTECTIVE EQUIPMENT - Due to the limited amount of gas in the cylinder, and the low release rate employed in instrument calibration, respiratory protection is not indicated under conditions of intended use.

ENGINEERING CONTROLS - Mechanical ventilation is suitable.

WORK PRACTICES - Avoid breathing gas. Use in well-ventilated areas. Follow the calibration procedure detailed in the MSA instruction manual provided with the instrument under calibration.

DATE OF PREPARATION - Rev. 2 Sept 2011

WARNING: This is a hazardous chemical product. By following the directions and warnings provided with this product, the hazards associated with the use of this product can be greatly reduced but never entirely eliminated. Mine Safety Appliances Company makes no warranties, expressed or implied, with respect to this product and EXPRESSLY DISCLAIMS THE WARRANTY OF MERCHANTABILITY AND ANY WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. Users assume all risks in handling, using or storing this product.