



MSDS032

Wasp - D.O.A. Plus

---

## MATERIAL SAFETY DATA SHEET

---

### Chemical Product and Company Identification

---

LABEL IDENTIFIER: Wasp - D.O.A. Plus™

PRODUCT IDENTIFIER: P/N 696194 Wasp D.O.A. Plus

COMPANY IDENTIFICATION: MINE SAFETY APPLIANCES COMPANY  
P.O. Box 439  
Pittsburgh, PA 15230  
CUSTOMER SERVICE: 1-800-MSA-2222 (8:30 a.m. – 5:00 p.m., USA local time)  
EMERGENCY: 1-800-255-3924 (CHEM-TEL, INC.)

---

### Vendor Information

---

**A Material Safety Data Sheet as furnished by Sherman - Williams Diversified Brands, Inc. for Wasp D.O.A. Plus is attached ( 4 Pages ).**

Sherman – Williams Diversified Brands, Inc. MSDS REVISION DATE: 1/26/99

---

### Other Information

---

WARNING: This is a hazardous chemical product. By following the directions and warnings provided with this product, the hazards associated with the use of this product can be greatly reduced but never entirely eliminated. Mine Safety Appliances Company makes no warranties, expressed or implied, with respect to this product and EXPRESSLY DISCLAIMS THE WARRANTY OF MERCHANTABILITY AND ANY WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. Users assume all risks in handling, using or storing this product.

MATERIAL SAFETY DATA SHEET

C22532  
01 00

MANUFACTURER'S NAME  
SHERWIN-WILLIAMS DIVERSIFIED BRANDS, INC  
26300 Fargo Avenue  
Bedford Heights, OH 44146

EMERGENCY TELEPHONE NO.  
(216) 566-2917

DATE OF PREPARATION  
26-JAN-99

INFORMATION TELEPHONE NO.  
(216) 292-7400

-----  
Section I -- PRODUCT IDENTIFICATION  
-----

PRODUCT NUMBER

C22532

HMIS CODES

Health 2  
Flammability 2  
Reactivity 0

PRODUCT NAME

696194 WASP D.O.A. PLUS

PRODUCT CLASS

Aerosol Specialty Product

-----  
Section II -- HAZARDOUS INGREDIENTS  
-----

INGREDIENT CAS No.	% by WT	ACGIH TLV	OSHA PEL	UNITS	V.P.
Mineral Spirits 160-Flash. 64742-47-8	4	Not Established			2.13
Heavy Aliphatic Solvent. 64742-96-7	88	Not Established			1.00
2-Propanol 67-63-0	6	400	400	PPM	33.00
		STEL	500	500	PPM
Piperonyl Butoxide. 51-03-6	0.3	Not Established			0.00
Carbon Dioxide 124-38-9	3	5000	5000	PPM	0.00

-----  
Section III -- PHYSICAL DATA  
-----

PRODUCT WEIGHT -- 6.62 lb./gal.    EVAPORATION RATE -- Faster than Ether  
SPECIFIC GRAVITY -- 0.80            VAPOR DENSITY -- Heavier than Air  
BOILING POINT -- <0 -500 F        MELTING POINT -- N.A.  
VOLATILE VOLUME -- 99 %            SOLUBILITY IN WATER -- N.A.  
VOLATILE WEIGHT -- 96.69 % (less Federally Exempt Solvents)  
HMIS -- 2    2    0

-----  
Section IV -- FIRE AND EXPLOSION HAZARD DATA  
-----

FLASH POINT                            LEL            UEL  
136 F TCC                            0.6            12.7  
EXTINGUISHING MEDIA  
Carbon Dioxide, Dry Chemical, Foam

Continued on page 2

-----  
UNUSUAL FIRE AND EXPLOSION HAZARDS

Isolate from heat, electrical equipment, sparks, and open flame. Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

## SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

-----  
Section V -- HEALTH HAZARD DATA-----  
ROUTES OF EXPOSURE

Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

## ACUTE Health Hazards

## EFFECTS OF OVEREXPOSURE

Irritation of eyes, skin and respiratory system. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

## SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

## MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

## EMERGENCY AND FIRST AID PROCEDURES

- If INHALED: If affected, remove from exposure. Restore breathing. Keep warm and quiet.
- If on SKIN: Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before re-use.
- If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.
- If SWALLOWED: Never give anything by mouth to an unconscious person. DO NOT INDUCE VOMITING. Give conscious patient several glasses of water. Seek medical attention.

## CHRONIC Health Hazards

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

-----  
Section VI -- REACTIVITY DATA-----  
STABILITY -- Stable  
CONDITIONS TO AVOID

None known.

## INCOMPATIBILITY

None known.

## HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

Continued on page 3

=====

HAZARDOUS POLYMERIZATION

Will not occur

=====

Section VII -- SPILL OR LEAK PROCEDURES

-----

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate and remove with inert absorbent.

WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

=====

Section VIII -- PROTECTION INFORMATION

-----

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section II is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section II.

PROTECTIVE GLOVES

None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact, wear chemical resistant gloves.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

=====

Section IX -- PRECAUTIONS

-----

DOL STORAGE CATEGORY

1A

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep away from heat and open flame.

Consult NFPA Code. Use approved Bonding and Grounding procedures.

Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally. Keep out of the reach of children.

OTHER PRECAUTIONS

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

=====

Section X -- OTHER REGULATORY INFORMATION

-----

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
---------	-------------------	---------	-----------

-----

No ingredients in this product are subject to SARA 313 (40 CFR 372.65C) Supplier Notification.

Continued on page 4

-----  
TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.