

Safety Data Sheet 50047MSA

Section 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1 Product identifier

Product Name . Flammable Gas Mixture Containing the Following Component in a

Nitrogen Balance Gas: Propane, 6.5-50.0%

MSA P/N . 10075801, 10075803, 10081605

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified use(s)• Calibration of Monitoring and Research Equipment

1.3 Details of the supplier of the safety data sheet

Manufacturer . Air Liquide U.S. Supplier Mine Safety Appliances Company

2700 Post Oak Blvd. 100 Cranberry Woods Drive Houston, TX 77056 Cranberry Township United States Pennsylvania U.S.A. 16066

www.us.airliquide.com 1-800-MSA-2222

sds@airliquide.com www.msanet.com/prism

Telephone (Technical) . 713-896-2896

Telephone (Technical) . 800-819-1704

1.4 Emergency telephone number

Manufacturer . 800-424-9300 - CHEMTREC

Manufacturer . +1 703-527-3887 - Outside United States

Section 2: Hazards Identification

EU/EEC

According to Regulation (EC) No 1272/2008 (CLP)/REACH 1907/2006 [amended by 453/2010] According to EU Directive 67/548/EEC (DSD) or 1999/45/EC (DPD)

2.1 Classification of the substance or mixture

CLP . Flammable Gases 1 - H220

Compressed Gas - H280

DSD/DPD . Extremely Flammable (F+)

R12

2.2 Label Elements

CLP

DANGER





Hazard statements • H220 - Extremely flammable gas

H280 - Contains gas under pressure; may explode if heated

Precautionary statements

Prevention • P210 - Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.

Response . P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 - Eliminate all ignition sources if safe to do so.

Storage/Disposal • P403 - Store in a well-ventilated place.

DSD/DPD



Risk phrases . R12 - Extremely flammable.

Safety phrases . S9 - Keep container in a well ventilated place

S16 - Keep away from sources of ignition - No Smoking.

2.3 Other Hazards

CLP This material is a simple asphyxiant. May displace or reduce oxygen available

for breathing especially in confined spaces.

According to Regulation (EC) No. 1272/2008 (CLP) this material is

considered hazardous.

This material is a simple asphyxiant. May displace or reduce oxygen available DSD/DPD

for breathing especially in confined spaces.

According to European Directive 1999/45/EC this material is considered dangerous.

United States (US)

According to OSHA 29 CFR 1910.1200 HCS

2.1 Classification of the substance or mixture

OSHA HCS 2012

 Flammable Gases 1 - H220 Compressed Gas - H280 Simple Asphyxiant

2.2 Label elements

OSHA HCS 2012

DANGER





Hazard statements . Extremely flammable gas - H220

Contains gas under pressure; may explode if heated -H280 May displace oxygen and cause rapid suffocation.

Precautionary statements

Prevention . Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking. - P210

Response . Leaking gas fire: Do not extinguish, unless leak can be stopped safely. - P377 Eliminate all ignition sources if safe to do so. - P381

Storage/Disposal . Store in a well-ventilated place. - P403

2.3 Other hazards

OSHA HCS 2012

 Under United States Regulations (29 CFR 1910.1200 - Hazard Communication) Standard), this product is considered hazardous.

Canada

According to WHMIS

2.1 Classification of the substance or mixture

WHMIS

 Compressed Gas - A Flammable Gases - B1

2.2 Label elements WHMIS





 Compressed Gas - A Flammable Gases - B1

2.3 Other hazards WHMIS

 This material is a simple asphyxiant. May displace or reduce oxygen available for breathing especially in confined spaces.
 In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

Section 3 - Composition/Information on Ingredients

3.1 Substances

• Material does not meet the criteria of a substance in accordance with Regulation (EC) No 1272/2008.

3.2 Mixtures

			Composition
Chemical Name	Identifiers	%	Classifications According to Regulation/Directive
	CAS:74-98-6		EU DSD/DPD: Annex VI, Table 3.2: F+ R12
Propane	EC Number:200-827-9	6.5% TO 50%	EU CLP: Annex VI, Table 3.1: Flam. Gas 1, H220; Press. Gas - Comp., H280
	EU Index:601-003-00-5		OSHA HCS 2012: Flam. Gas 1; Press. Gas - Comp.; Simp. Asphyx.
	CAS.7707 27 0		EU DSD/DPD: Not Classified
Nitrogen	CAS:7727-37-9 EINECS:231-783-9	Balance	EU CLP: Self Classified: Press. Gas - Comp. H280
	EINEC3.231-763-9		OSHA HCS 2012: Press. Gas - Comp.; Simp. Asphyx.

Section 4 - First Aid Measures

4.1 Description of first aid measures

Inhalation

• IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. If signs/symptoms continue, get medical attention.

Skin

• Although exposure is unlikely, in case of contact immediately flush skin with running water. If skin irritation develops get medical advice/attention.

Eye

• First aid is not expected to be necessary if material is used under ordinary conditions and as recommended. If eye irritation persists: Get medical advice/attention.

Ingestion

Ingestion is not considered a potential route of exposure.

4.2 Most important symptoms and effects, both acute and delayed

Refer to Section 11 - Toxicological Information.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to Physician

. All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

4.4 Other information

Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. RESCUERS SHOULD NOT ATTEMPT TO RETRIEVE VICTIMS OF EXPOSURE TO GASES WITHOUT ADEQUATE PERSONAL PROTECTIVE EQUIPMENT. At a minimum, Self-Contained Breathing Apparatus must be worn. Victim(s) who experience any adverse effect after overexposure to this gas mixture must be taken for medical attention. Rescuers should be taken for medical attention if necessary. Take a copy of the label and the MSDS to physician or other health professional with victim(s).

Section 5 - Firefighting Measures

5.1 Extinguishing media

Suitable Extinguishing Media . SMALL FIRES: Dry chemical or CO2. LARGE FIRES: Water spray or fog.

Unsuitable Extinguishing Media

No data available

5.2 Special hazards arising from the substance or mixture

Unusual Fire and Explosion Hazards

EXTREMELY FLAMMABLE

Will form explosive mixtures with air.

Vapors may travel to source of ignition and flash back.

Cylinders exposed to fire may vent and release flammable gas through pressure

relief devices.

Containers may explode when heated.

Ruptured cylinders may rocket.

Hazardous Combustion Products

No data available

5.3 Advice for firefighters

Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

Wear positive pressure self-contained breathing apparatus (SCBA).

DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED Move containers from fire area if you can do it without risk.

FIRE: If tank, rail car or tank truck is involved in a fire, ISOLATE for 1600 meters

(1 mile) in all directions; also, consider initial evacuation for 1600 meters (1 mile) in all directions.

FIRE INVOLVING TANKS: ALWAYS stay away from tanks engulfed in fire. FIRE INVOLVING TANKS: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.

FIRE INVOLVING TANKS: Withdraw immediately in case of rising sound from

venting safety devices or discoloration of tank. FIRE INVOLVING TANKS: Cool containers with flooding quantities of water until

well after fire is out.

FIRE INVOLVING TANKS: Do not direct water at source of leak or safety devices; icing may occur.

FIRE INVOLVING TANKS: For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

Section 6 - Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal Precautions

 Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material. Ventilate the area before entry.

Emergency Procedures

 ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). As an immediate precautionary measure, isolate spill or leak area for at least 100 meters (330 feet) in all directions. Stop leak if you can do it without risk. Keep unauthorized personnel away. Keep out of low areas. Stay upwind. LARGE SPILL: Consider initial downwind evacuation for at least 800 meters (1/2 mile)

6.2 Environmental precautions

Prevent spreading of vapors through sewers, ventilation systems and confined areas.

6.3 Methods and material for containment and cleaning up

Containment/Clean-up Measures

All equipment used when handling the product must be grounded. Stop leak if you can do it without risk.
 If possible, turn leaking containers so that gas escapes rather than liquid.
 Use water spray to reduce vapors; do not put water directly on leak, spill area or inside container.
 Do not direct water at spill or source of leak. Isolate area until gas has dispersed.

6.4 Reference to other sections

 Refer to Section 8 - Exposure Controls/Personal Protection and Section 13 -Disposal Considerations.

Section 7 - Handling and Storage

7.1 Precautions for safe handling

Handling

• Keep away from heat and ignition sources – No Smoking. Take precautionary measures against static charges. All equipment used when handling the product must be grounded. Use only non-sparking tools. Use only with adequate ventilation. Ventilate closed spaces before entering. Be aware of any signs of dizziness or fatigue, especially if work is done in a poorly ventilated area; exposures to fatal concentrations of this gas mixture could occur without any significant warning symptoms, due to olfactory fatigue or oxygen deficiency. Cylinders should be firmly secured to prevent falling or being knocked-over. Use explosion-proof - electrical, ventilating and/or lighting equipment. Do not attempt to repair, adjust, or in any other way modify cylinders. If there is a malfunction or another type of operational problem, contact nearest distributor immediately. Empty containers retain product residue and can be hazardous. Do not cut, weld, puncture or incinerate container.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Cylinders should be stored in dry, well-ventilated areas away from sources of heat, ignition and direct sunlight. Do not allow area where cylinders are stored to exceed 52C (125F). Cylinders must be protected from the environment, and preferably kept at room temperature approximately 21C (70F). Protect cylinders against physical damage. Cylinders should be firmly secured to prevent falling or being knocked-over. Store locked up.

7.3 Specific end use(s)

Refer to Section 1.2 - Relevant identified uses.

Section 8 - Exposure Controls/Personal Protection

8.1 Control parameters

Exposure Limits/Guidelines

Currently there are no applicable exposure limits established for this material.

Exposure Control Notations

Portugal

• Nitrogen (7727-37-9): Simple Asphyxiants: (Simple Asphyxiant)

Ireland

•Nitrogen (7727-37-9): Simple Asphyxiants: (Asphyxiant)

• Propane (74-98-6): Simple Asphyxiants: (Asphyxiant)

Spain

•Nitrogen (7727-37-9): Simple Asphyxiants: (simple asphyxiant)

Germany DFG

• Propane (74-98-6): **Pregnancy:** (classification not yet possible)

8.2 Exposure controls

Engineering Measures/Controls

 Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof - electrical, ventilating and/or lighting equipment.

Personal Protective Equipment

Respiratory

. In case of insufficient ventilation, wear suitable respiratory equipment.

Eye/Face

Wear safety glasses.

Skin/Body

. Wear leather gloves when handling cylinders.

Environmental Exposure

Controls

Follow best practice for site management and disposal of waste. Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways.

Section 9 - Physical and Chemical Properties

9.1 Information on Physical and Chemical Properties

Material Description			
Physical Form	Gas	Appearance/Description	Colorless gas with no odor.
Color	Colorless	Odor	Odorless
Odor Threshold	Data lacking		
General Properties			
Boiling Point	Data lacking	Melting Point	Data lacking
Decomposition Temperature	Data lacking	рН	Not relevant
Specific Gravity/Relative Density	Data lacking	Water Solubility	Data lacking
Viscosity	Data lacking	Explosive Properties	Data lacking
Oxidizing Properties:	Data lacking		
Volatility			
Vapor Pressure	Data lacking	Vapor Density	Data lacking
Evaporation Rate	Data lacking		
Flammability			
Flash Point	-104 C(-155.2 F) CC (Closed Cup) (Propane)	UEL	9.5 % (Propane)
LEL	2.2 %	Autoignition	450 C(842 F)
LEL	(Propane)	Autoignition	(Propane)
Flammability (solid, gas)	Flammable Gas.		
Environmental		·	
Octanol/Water Partition coefficient	Data lacking		

9.2 Other Information

No additional physical and chemical parameters noted.

Section 10: Stability and Reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal temperatures and pressures.

10.3 Possibility of hazardous reactions

. Hazardous polymerization will not occur.

10.4 Conditions to avoid

Excess heat, sparks, open flame.

10.5 Incompatible materials

Propane is incompatible with strong oxidizers. Nitrogen reacts with Li, Nd, and Ti at high temperatures.

10.6 Hazardous decomposition products

• The Propane component of this gas mixture will thermally decompose into carbon monoxide and carbon dioxide.

Section 11 - Toxicological Information

11.1 Information on toxicological effects

GHS Properties	Classification
GRS Properties	Classification
Acute toxicity	EU/CLP • Data lacking
	OSHA HCS 2012 • Data lacking
Aspiration Hazard	EU/CLP • Data lacking
7 Op. 1 a. 1 C. 1 . 1 . 2 . 2	OSHA HCS 2012 • Data lacking
Carcinogenicity	EU/CLP ◆ Data lacking
our onlogomonty	OSHA HCS 2012 • Data lacking
Germ Cell Mutagenicity	EU/CLP • Data lacking
John John Matagonion,	OSHA HCS 2012 • Data lacking
Skin corrosion/Irritation	EU/CLP • Data lacking
	OSHA HCS 2012 • Data lacking
Skin sensitization	EU/CLP ◆ Data lacking
OKIN SONSKIZUKON	OSHA HCS 2012 • Data lacking
STOT-RE	EU/CLP ◆ Data lacking
OTOT KE	OSHA HCS 2012 • Data lacking
STOT-SE	EU/CLP ◆ Data lacking
0101 02	OSHA HCS 2012 • Data lacking
Toxicity for Reproduction	EU/CLP ◆ Data lacking
Toxicity for respirate tion	OSHA HCS 2012 • Data lacking
Respiratory sensitization	EU/CLP ◆ Data lacking
Respiratory Scholitzation	OSHA HCS 2012 • Data lacking
Serious eye damage/Irritation	EU/CLP ◆ Data lacking
Jenous eye damaye/irritation	OSHA HCS 2012 • Data lacking

Potential Health Effects

Inhalation

Acute (Immediate)

This material is a simple asphyxiant. May displace or reduce oxygen available for breathing especially in confined spaces. If this material is released in a small, poorly ventilated area (i.e. an enclosed or confined space), an oxygen-deficient environment may occur. Individuals breathing such an atmosphere may experience symptoms which include headaches, ringing in ears, dizziness, drowsiness, unconsciousness, nausea, vomiting, and depression of all the senses. Under some circumstances of over-exposure, death may occur. The following effects associated with decreased levels of oxygen: increase in breathing and pulse rate, emotional upset, abnormal fatigue, nausea, vomiting, collapse, loss of consciousness, convulsive movements, respiratory collapse and death.

Chronic (Delayed)

No data available

Skin

Acute (Immediate)

Under normal conditions of use, no health effects are expected.

Chronic (Delayed)

No data available

Eve

Acute (Immediate)

Under normal conditions of use, no health effects are expected.

Chronic (Delayed)

No data available

Ingestion

Acute (Immediate)

Ingestion is not anticipated to be a likely route of exposure to this product.

Chronic (Delayed)

No data available

Section 12 - Ecological Information

12.1 Toxicity

Material data lacking.

12.2 Persistence and degradability

Material data lacking.

12.3 Bioaccumulative potential

Material data lacking.

12.4 Mobility in Soil

Material data lacking.

12.5 Results of PBT and vPvB assessment

No PBT and vPvB assessment has been conducted.

12.6 Other adverse effects

No studies have been found.

Section 13 - Disposal Considerations

13.1 Waste treatment methods

Product waste

 Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

 Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	14.1 UN number	14.2 UN proper shipping name	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards
DOT	UN1954	Compressed gas, flammable, n.o.s. (Propane, Nitrogen)	2.1	NDA	NDA
TDG	UN1954	COMPRESSED GAS, FLAMMABLE, N.O.S. (Propane, Nitrogen)	2.1	NDA	Potential Marine Pollutant
IMO/IMDG	UN1954	COMPRESSED GAS, FLAMMABLE, N.O.S. (Propane, Nitrogen)	2.1	NDA	NDA
IATA/ICAO	UN1954	Compressed gas, flammable, n.o.s. (Propane, Nitrogen)	2.1	NDA	NDA

14.6 Special precautions for user

- Cylinders should be transported in a secure position, in a well-ventilated vehicle.
 The transportation of compressed gas cylinders in automobiles or in closed-body
 vehicles can present serious safety hazards. If transporting these cylinders in
 vehicles, ensure these cylinders are not exposed to extremely high temperatures
 (as may occur in an enclosed vehicle on a hot day). Additionally, the vehicle should
 be well-ventilated during transportation.
- 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
- Data lacking.

Section 15 - Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications • Acute, Fire, Pressure(Sudden Release of)

	-	State Right	t To Know	
Component	CAS	MA	NJ	PA
Nitrogen	7727-37-9	Yes	Yes	Yes
Propane	74-98-6	Yes	Yes	Yes

			Inventory				
Component	CAS	Canada DSL	Canada NDSL	Ch	ina	EU EINECS	EU ELNICS
Nitrogen	7727-37-9	Yes	No	Y	es	Yes	No
Propane	74-98-6	Yes	No	Y	es	Yes	No
			Inventory (Co	n't.)			
Component			CAS		TS	CA	
Nitrogen		772	27-37-9		Υe	es	
Propane		74-	98-6		Υe	es	

Canada

Canada - WHMIS - Classifications of Substances		
• Propane	74-98-6	A, B1
Nitrogen	7727-37-9	A
Canada - WHMIS - Ingredient Disclosure List		
Propane	74-98-6	Not Listed

Nitrogen	7727-37-9	Not Listed
nvironment		
Canada - CEPA - Priority Substances List		
• Propane	74-98-6	Not Listed
• Nitrogen	7727-37-9	Not Listed
Thirdge.		Not Elotod
nina		
nvironment		
China - Ozone Depleting Substances - First Schedule		
Propane	74-98-6	Not Listed
Nitrogen	7727-37-9	Not Listed
China - Ozone Depleting Substances - Second Schedule		
• Propane	74-98-6	Not Listed
Nitrogen	7727-37-9	Not Listed
China - Ozone Depleting Substances - Third Schedule		
• Propane	74-98-6	Not Listed
• Nitrogen	7727-37-9	Not Listed
Milogen	1121-01-9	Not Listed
)ther		
China - Annex I & II - Controlled Chemicals Lists		
Propane	74-98-6	Not Listed
• Nitrogen	7727-37-9	Not Listed
China - Dangerous Goods List		
• Propane	74-98-6	
• Nitrogen	7727-37-9	(compressed or refrigerated liquid)
		,
China - Export Control List - Part I Chemicals		
• Propane	74-98-6	Not Listed
Nitrogen	7727-37-9	Not Listed
ırope		
Other		
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Classification	74.00.0	F: D40
• Propane	74-98-6	F+; R12
Nitrogen	7727-37-9	Not Listed
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Concentration Limits		
• Propane	74-98-6	Not Listed
• Nitrogen	7727-37-9	Not Listed
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Labelling		
• Propane	74-98-6	F+ R:12 S:(2)-9-16
• Nitrogen	7727-37-9	Not Listed
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Notes - Substances and Preparations		
• Propane	74-98-6	Not Listed
	7 1 00 0	. TOL LIGIOU
• Nitrogen	7727-37-9	Not Listed

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Safety Phrases		
• Propane	74-98-6	S:(2)-9-16
Nitrogen	7727-37-9	Not Listed
ermany		
Environment		
Germany - TA Luft - Types and Classes		
Propane	74-98-6	Not Listed
Nitrogen	7727-37-9	Not Listed
Germany - Water Classification (VwVwS) - Annex 1		
• Propane	74-98-6	ID Number 560, not consider hazardous to water
• Nitrogen	7727-37-9	ID Number 1351, not considered hazardous to water
Germany - Water Classification (VwVwS) - Annex 2 - Water Hazard Classes		
• Propane	74-98-6	Not Listed
• Nitrogen	7727-37-9	Not Listed
Germany - Water Classification (VwVwS) - Annex 3		
• Propane	74-98-6	Not Listed
• Nitrogen	7727-37-9	Not Listed
Other Transcription of the Control o		
Germany - Specifically Regulated Chemicals in TRGS		
• Propane	74-98-6	Not Listed
Nitrogen	7727-37-9	Not Listed
ortugal		
Other		

Other		
Portugal - Prohibited Substances		
• Propane	74-98-6	Not Listed
Nitrogen	7727-37-9	Not Listed

United Kingdom

Air		
74-98-6	Not Listed	
7727-37-9	Not Listed	
		_
74-98-6	Not Listed	
7727-37-9	Not Listed	
74-98-6	Not Listed	
7727-37-9	Not Listed	
•	74-98-6 7727-37-9 74-98-6 7727-37-9 74-98-6	74-98-6 Not Listed 7727-37-9 Not Listed 74-98-6 Not Listed 7727-37-9 Not Listed 74-98-6 Not Listed

United States

Propane	74-98-6	Not Listed
Nitrogen	7727-37-9	Not Listed
J.S OSHA - Specifically Regulated Chemicals		
• Propane	74-98-6	Not Listed
• Nitrogen	7727-37-9	Not Listed
vironment		
J.S CAA (Clean Air Act) - 1990 Hazardous Air Pollutants		
Propane	74-98-6	Not Listed
Nitrogen	7727-37-9	Not Listed
U.S CERCLA/SARA - Hazardous Substances and their Reportable Quantities		
• Propane	74-98-6	Not Listed
• Nitrogen	7727-37-9	Not Listed
U.S CERCLA/SARA - Radionuclides and Their Reportable Quantities		
• Propane	74-98-6	Not Listed
• Nitrogen	7727-37-9	Not Listed
U.S CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs		
• Propane	74-98-6	Not Listed
• Nitrogen	7727-37-9	Not Listed
U.S CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs		
• Propane	74-98-6	Not Listed
• Nitrogen	7727-37-9	Not Listed
U.S CERCLA/SARA - Section 313 - Emission Reporting		
• Propane	74-98-6	Not Listed
Nitrogen	7727-37-9	Not Listed
J.S CERCLA/SARA - Section 313 - PBT Chemical Listing		
• Propane	74-98-6	Not Listed
• Nitrogen	7727-37-9	Not Listed

United States - California

Environment			
U.S California - Proposition 65 - Carcinogens List			
• Propane	74-98-6	Not Listed	
Nitrogen	7727-37-9	Not Listed	
U.S California - Proposition 65 - Developmental Toxicity			
• Propane	74-98-6	Not Listed	
• Nitrogen	7727-37-9	Not Listed	
U.S California - Proposition 65 - Maximum Allowable Dose Levels (MADL)			
• Propane	74-98-6	Not Listed	
• Nitrogen	7727-37-9	Not Listed	
U.S California - Proposition 65 - No Significant Risk Levels (NSRL)			
• Propane	74-98-6	Not Listed	

Nitrogen	7727-37-9	Not Listed	
U.S California - Proposition 65 - Reproductive Toxicity - Fer	male		
Propane	74-98-6	Not Listed	
Nitrogen	7727-37-9	Not Listed	
U.S California - Proposition 65 - Reproductive Toxicity - Ma	le		
• Propane	74-98-6	Not Listed	
Nitrogen	7727-37-9	Not Listed	

United States - Pennsylvania

_abor U.S Pennsylvania - RTK (Right to Know) - Environmen	stal Hazard Liet	
Propane	74-98-6	Not Listed
• Nitrogen	7727-37-9	Not Listed
U.S Pennsylvania - RTK (Right to Know) - Special Haza	ardous Substances	
• Propane	74-98-6	Not Listed
Nitrogen	7727-37-9	Not Listed

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out.

Section 16 - Other Information

Last Revision Date Preparation Date Disclaimer/Statement of Liability

- 05/September/2014
- . 05/September/2014
- To the best of Air Liquide's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this gas mixture is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

Key to abbreviationsNDA = No Data Available