

Safety Data Sheet 50213 according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules

and Regulations Date of issue: 08/15/2014

Revision date: 09/23/2015

Version: 2.0

Product form Product name MSA PN 1.2. Releva					
MSA PN		: Mixture			
		: Oxygen (15 - 23.5%,) Pent Sulfide(0.001-0.025%, 10		75%,) Carbon Monoxide (0.0005-0.09 m) in balance Nitrogen	1%,5-900ppm) Hydroger
1.2. Releva		: 10125708, 10007049,101	25947		
	nt identified uses of the su	Ibstance or mixture and uses a	dvised aga	ainst	
Use of the subst	ince/mixture	: Test gas/Calibration gas.			
1.3. Detail	of the supplier of the safe	ty data sheet			
	821 Chesapeake Driv Cambridge, MD 2161 410-901-8644		OR	Portagas Inc. Division of Praxair 1202 E. Sam Houston Parkway S. Pasadena, TX 77503 1-800-548-2268	
	1-800-MSA-2222 www	es Company, 1000 Cranberry Wood w.msasafety.com	ls Drive, Crar	berry Twp, PA 16066	
1-800-MSA-2222 www.msanet.co					
1.4. Emerç	ency telephone number				
Emergency num	er	: CHEMTREC: 1-800-424- Internationally: 1-703-527			
	Hazards identificatior				
2.1. Classi	fication of the substance of	r mixture			
Classification (HS-US)				
Compressed gas	H280				
2.2. Label	elements				
GHS-US labelin	3				
1 1 1 4	ns (GHS-US)				
Hazard pictograr		GHS04			
⊣azard pictograr Signal word (GH	3-US)	GHS04 : Warning			
			er pressure	may explode if heated	

No additional information available

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.4. Unknown acute toxicity (GHS-US)

SECTION 4: Eirst aid moasuro

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture			
Name	Product identifier	%	Classification (GHS-US)
Nitrogen	(CAS No) 7727-37-9	75.635 - 80.9985	Compressed gas, H280
Oxygen	(CAS No) 7782-44-7	15 - 23.5	Ox. Gas 1, H270 Compressed gas, H280
Pentane	(CAS No) 109-66-0	0 - 0.75	Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304
Carbon monoxide	(CAS No) 630-08-0	0.0005 - 0.09	Flam. Gas 1, H220 Compressed gas, H280 Acute Tox. 3 (Inhalation:gas), H331 Repr. 1A, H360 STOT RE 1, H372
Hydrogen sulfide	(CAS №) 7783-06-4	0.001 - 0.0025	Flam. Gas 1, H220 Liquefied gas, H280 Acute Tox. 2 (Inhalation:gas), H330 STOT SE 3, H335

SECTION 4: First aid measures			
4.1. Description of first aid measure	es		
First-aid measures after inhalation	: Adverse effects not expected f	rom this product. If you feel unwell, seek m	redical advice.
First-aid measures after skin contact	: Adverse effects not expected f		
First-aid measures after eye contact	: Adverse effects not expected f	om this product.	
First-aid measures after ingestion	: Ingestion is not considered a p	otential route of exposure.	
4.2. Most important symptoms and	effects, both acute and delayed		
Symptoms/injuries	: Adverse effects not expected	from this product.	
Symptoms/injuries after inhalation	: Adverse effects not expected	from this product.	
Symptoms/injuries after skin contact	: Adverse effects not expected	from this product.	
Symptoms/injuries after eye contact	: Adverse effects not expected f	om this product.	
Symptoms/injuries after ingestion	: Ingestion is not considered a p	otential route of exposure.	
Symptoms/injuries upon intravenous administration	: Not known.		
Chronic symptoms	: Adverse effects not expected f	rom this product.	
4.3. Indication of any immediate me	edical attention and special treatment	needed	
If you feel unwell, seek medical advice. If be	eathing is difficult, give oxygen.		
SECTION 5: Firefighting measur	es		
5.1. Extinguishing media			
Suitable extinguishing media	: Use extinguishing media appro	priate for surrounding fire.	
Unsuitable extinguishing media	: Do not use water jet.		
5.2. Special hazards arising from th	e substance or mixture		
Fire hazard	: The product is not flammable.		
Explosion hazard	: Product is not explosive. Heat and increasing risk of burns ar	may build pressure, rupturing closed conta d injuries.	liners, spreading fire
Reactivity	: None under recommended sto	rage and handling conditions (see section	7).
5.3. Advice for firefighters			
Firefighting instructions		Fight fire remotely due to the risk of explos ners. Exercise caution when fighting any ch	
09/23/2015	EN (English US)	SDS ID: 50213	2

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Protection during firefighting	: Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Do not enter fire area without proper protective equipment, including respiratory protection.
SECTION 6: Accident	release measures
6.1. Personal precauti	ns, protective equipment and emergency procedures
General measures	: Ensure adequate ventilation.
6.1.1. For non-emergene	personnel
Protective equipment	: Wear protective equipment consistent with the site emergency plan.
Emergency procedures	: Escape the danger area by the closest safe route. Close doors and windows of adjacent premises. Keep containers closed. Mark the danger area. Seal off low-lying areas. Keep upwind.
6.1.2. For emergency res	onders
Protective equipment	: Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Equip cleanup crew with proper protection.
Emergency procedures	: Evacuate and limit access. Ventilate area.
6.2. Environmental pre	autions
Try to stop release if safe to o	so. None.
6.3. Methods and mate	al for containment and cleaning up
For containment	: Try to stop release if safe to do so.
Methods for cleaning up	: Dispose of this material and its container in accordance with local regulations.
6.4. Reference to othe	ections
See also Sections 8 and 13.	
SECTION 7: Handling	nd storage
7.1. Precautions for sa	handling
Additional hazards when proc	 Pressurized container: Do not pierce or burn, even after use. Use equipment rated for cylinder pressure.
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area.
Hygiene measures	: Do not eat, drink or smoke when using this product.
7.2. Conditions for saf	storage, including any incompatibilities
Technical measures	: Comply with applicable regulations.
Storage conditions	: Do not expose to temperatures exceeding 52°C (125°F). Keep container closed when not in use. Protect cylinder from physical damage. Store in well ventilated area.
Incompatible products	: None known.
Incompatible materials	: Flammable materials.
7.3. Specific end use(s	
Test gas/Calibration gas.	
SECTION 8: Exposure	controls/personal protection

8.1. Control parameters

Pentane (109-66-0)		
USA ACGIH	ACGIH TWA (ppm)	600 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	2950 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm

Carbon monoxide (630-08-0)		
USA ACGIH	ACGIH TWA (ppm)	25 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	55 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hydrogen sulfide (7783-06-4)		
USA ACGIH	ACGIH TWA (ppm	n)	1 ppm
USA ACGIH	ACGIH STEL (ppn	n)	5 ppm
USA OSHA	OSHA PEL (Ceilin	ıg) (ppm)	20 ppm
Nitrogen (7727-37-9)			
8.2. Exposure controls			
Appropriate engineering contro	s :	1 0	exhaust ventilation. Systems under pressure should be re exposure is below occupational exposure limits. maintenance activities.
Hand protection	:	Wear working gloves when handling	gas containers. 29CFR 1910.138: Hand Protection.
Eye protection	:	Wear safety glasses with side shields	s. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection	:	Wear suitable protective clothing, e.g	lab coats, coveralls or flame resistant clothing.
Respiratory protection : None necessary during normal and routine operations.		outine operations.	

: None necessary during normal and routine operations.

specific methods for waste gas treatment. None necessary.

: Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for

: Wear safety shoes while handling containers. 29 CFR 1910.136: Foot Protection.

Thermal hazard protection Environmental exposure controls

Other information

SECTION 9: Physical and chemical properties				
9.1. Information on basic physical and chemical properties				
Physical state	: Gas			
Molecular mass	: Not applicable for gas-mixtures.			
Color	: Mixture contains one or more component(s) which have the following colour(s): Colourless., Colorless			
Odor	 There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odour(s): No odour warning properties., gasoline-like, Odourless., Poor warning properties at low concentrations., Odour can persist., Rotten eggs. 			
Odor threshold	: No data available			
рН	: Not applicable for gas-mixtures.			
Relative evaporation rate (butyl acetate=1)	: No data available			
Relative evaporation rate (ether=1)	: Not applicable for gas-mixtures.			
Melting point	: No data available			
Freezing point	: No data available			
Boiling point	: No data available			
Flash point	: No data available			
Auto-ignition temperature	: No data available			
Decomposition temperature	: No data available			
Flammability (solid, gas)	: No data available			
Vapor pressure	: Not applicable.			
Relative vapor density at 20 °C	: No data available			
Relative density	: No data available			
Relative gas density	: Lighter or similar to air.			
Solubility	 Water: Solubility in water of component(s) of the mixture : •: 39 mg/l •: <1 mg/l •: Insoluble •: 3980 mg/l •: 20 mg/l 			
Log Pow	: Not applicable for gas-mixtures.			
Log Kow	: Not applicable for gas-mixtures.			
Viscosity, kinematic	: Not applicable.			
Viscosity, dynamic	: Not applicable.			
Explosive properties	: Not applicable.			
Oxidizing properties	: None.			

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosive limits	: No data available			
.2. Other information				
dditional information	: None.			
ECTION 10: Stability and rea	ctivity			
0.1. Reactivity				
lone under recommended storage and	nandling conditions (see section 7).			
0.2. Chemical stability				
Stable under recommended handling an	d storage conditions (see section 7).			
0.3. Possibility of hazardous read	Possibility of hazardous reactions			
Can form explosive mixtures with flamma				
0.4. Conditions to avoid				
None under recommended storage and	nandling conditions (see section 7).			
0.5. Incompatible materials				
Flammable materials.				
	raduete			
0.6. Hazardous decomposition p				
-	use hazardous decomposition products should not be produced.			
SECTION 11: Toxicological inf				
1.1. Information on toxicological	effects			
cute toxicity	: Not classified			
Oxygen (7782-44-7)	400000 ppm/4h			
LC50 inhalation rat (ppm)	400000 ppm/4n			
,				
Pentane (109-66-0)				
Pentane (109-66-0) LD50 dermal rabbit	3000 mg/kg			
Pentane (109-66-0) LD50 dermal rabbit LC50 inhalation rat (mg/l)	3000 mg/kg 364 g/m³ (Exposure time: 4 h)			
Pentane (109-66-0) LD50 dermal rabbit LC50 inhalation rat (mg/l) LC50 inhalation rat (ppm)	3000 mg/kg 364 g/m³ (Exposure time: 4 h) 123390 ppm/4h			
Pentane (109-66-0) LD50 dermal rabbit LC50 inhalation rat (mg/l) LC50 inhalation rat (ppm) ATE US (dermal)	3000 mg/kg 364 g/m³ (Exposure time: 4 h) 123390 ppm/4h 3000.00000000 mg/kg body weight			
Pentane (109-66-0) LD50 dermal rabbit LC50 inhalation rat (mg/l) LC50 inhalation rat (ppm) ATE US (dermal)	3000 mg/kg 364 g/m³ (Exposure time: 4 h) 123390 ppm/4h			
Pentane (109-66-0) LD50 dermal rabbit LC50 inhalation rat (mg/l) LC50 inhalation rat (ppm) ATE US (dermal) ATE US (gases) ATE US (vapors)	3000 mg/kg 364 g/m³ (Exposure time: 4 h) 123390 ppm/4h 3000.0000000 mg/kg body weight 123390.00000000 ppmV/4h			
Pentane (109-66-0) LD50 dermal rabbit LC50 inhalation rat (mg/l) LC50 inhalation rat (ppm) ATE US (dermal) ATE US (gases) ATE US (vapors) ATE US (dust, mist)	3000 mg/kg 364 g/m³ (Exposure time: 4 h) 123390 ppm/4h 3000.00000000 mg/kg body weight 123390.0000000 ppmV/4h 364.0000000 mg/l/4h			
Pentane (109-66-0) LD50 dermal rabbit LC50 inhalation rat (mg/l) LC50 inhalation rat (ppm) ATE US (dermal) ATE US (gases) ATE US (gases) ATE US (vapors) ATE US (dust, mist) Carbon monoxide (630-08-0)	3000 mg/kg 364 g/m³ (Exposure time: 4 h) 123390 ppm/4h 3000.00000000 mg/kg body weight 123390.00000000 ppmV/4h 364.00000000 mg/l/4h 364.00000000 mg/l/4h			
Pentane (109-66-0) LD50 dermal rabbit LC50 inhalation rat (mg/l) LC50 inhalation rat (ppm) ATE US (dermal) ATE US (gases) ATE US (gases) ATE US (vapors) ATE US (dust, mist) Carbon monoxide (630-08-0) LC50 inhalation rat (ppm)	3000 mg/kg 364 g/m³ (Exposure time: 4 h) 123390 ppm/4h 3000.00000000 mg/kg body weight 123390.0000000 ppmV/4h 364.0000000 mg/l/4h			
Pentane (109-66-0) LD50 dermal rabbit LC50 inhalation rat (mg/l) LC50 inhalation rat (ppm) ATE US (dermal) ATE US (gases) ATE US (vapors) ATE US (dust, mist) Carbon monoxide (630-08-0) LC50 inhalation rat (ppm) ATE US (gases)	3000 mg/kg 364 g/m³ (Exposure time: 4 h) 123390 ppm/4h 3000.00000000 mg/kg body weight 123390.0000000 ppmV/4h 364.0000000 mg/l/4h 364.0000000 mg/l/4h 1880 ppm/4h			
Pentane (109-66-0) LD50 dermal rabbit LC50 inhalation rat (mg/l) LC50 inhalation rat (ppm) ATE US (dermal) ATE US (gases) ATE US (gases) ATE US (vapors) ATE US (dust, mist) Carbon monoxide (630-08-0) LC50 inhalation rat (ppm) ATE US (gases) Hydrogen sulfide (7783-06-4)	3000 mg/kg 364 g/m³ (Exposure time: 4 h) 123390 ppm/4h 3000.0000000 mg/kg body weight 123390.0000000 ppmV/4h 364.0000000 mg/l/4h 364.0000000 mg/l/4h 1880 ppm/4h 1880.0000000 ppmV/4h			
Pentane (109-66-0) LD50 dermal rabbit LC50 inhalation rat (mg/l) LC50 inhalation rat (ppm) ATE US (dermal) ATE US (gases) ATE US (gases) ATE US (dust, mist) Carbon monoxide (630-08-0) LC50 inhalation rat (ppm) ATE US (gases) Hydrogen sulfide (7783-06-4) LC50 inhalation rat (mg/l)	3000 mg/kg 364 g/m³ (Exposure time: 4 h) 123390 ppm/4h 3000.00000000 mg/kg body weight 123390.0000000 ppmV/4h 364.0000000 mg/l/4h 364.0000000 mg/l/4h 1880 ppm/4h			
Pentane (109-66-0) LD50 dermal rabbit LC50 inhalation rat (mg/l) LC50 inhalation rat (ppm) ATE US (dermal) ATE US (gases)	3000 mg/kg 364 g/m³ (Exposure time: 4 h) 123390 ppm/4h 3000.0000000 mg/kg body weight 123390.0000000 ppmV/4h 364.0000000 mg/l/4h 364.0000000 mg/l/4h 1880 ppm/4h 1880 ppm/4h 1880.0000000 ppmV/4h 0.99 mg/l (Exposure time: 1 h) 356 ppm/4h 356.0000000 ppmV/4h			
Pentane (109-66-0)LD50 dermal rabbitLC50 inhalation rat (mg/l)LC50 inhalation rat (ppm)ATE US (dermal)ATE US (gases)ATE US (vapors)ATE US (dust, mist)Carbon monoxide (630-08-0)LC50 inhalation rat (ppm)ATE US (gases)Hydrogen sulfide (7783-06-4)LC50 inhalation rat (mg/l)LC50 inhalation rat (ppm)ATE US (gases)	3000 mg/kg 364 g/m³ (Exposure time: 4 h) 123390 ppm/4h 3000.0000000 mg/kg body weight 123390.0000000 ppmV/4h 364.0000000 mg/l/4h 364.0000000 mg/l/4h 1880 ppm/4h 1880.0000000 ppmV/4h 0.99 mg/l (Exposure time: 1 h) 356 ppm/4h			
Pentane (109-66-0) LD50 dermal rabbit LC50 inhalation rat (mg/l) LC50 inhalation rat (ppm) ATE US (dermal) ATE US (dermal) ATE US (gases) ATE US (vapors) ATE US (dust, mist) Carbon monoxide (630-08-0) LC50 inhalation rat (ppm) ATE US (gases) Hydrogen sulfide (7783-06-4) LC50 inhalation rat (mg/l) LC50 inhalation rat (ppm) ATE US (gases) ATE US (gases) ATE US (gases)	3000 mg/kg 364 g/m³ (Exposure time: 4 h) 123390 ppm/4h 3000.0000000 mg/kg body weight 123390.0000000 ppmV/4h 364.0000000 mg/l/4h 364.0000000 mg/l/4h 1880 ppm/4h 1880 ppm/4h 1880.0000000 ppmV/4h 0.99 mg/l (Exposure time: 1 h) 356 ppm/4h 356.0000000 ppmV/4h			
Pentane (109-66-0) LD50 dermal rabbit LC50 inhalation rat (mg/l) LC50 inhalation rat (ppm) ATE US (dermal) ATE US (dermal) ATE US (gases) ATE US (vapors) ATE US (dust, mist) Carbon monoxide (630-08-0) LC50 inhalation rat (ppm) ATE US (gases) Hydrogen sulfide (7783-06-4) LC50 inhalation rat (mg/l) LC50 inhalation rat (ppm) ATE US (gases) ATE US (gases) ATE US (gases)	3000 mg/kg 364 g/m³ (Exposure time: 4 h) 123390 ppm/4h 3000.00000000 mg/kg body weight 123390.00000000 ppmV/4h 364.00000000 mg/l/4h 364.00000000 mg/l/4h 1880 ppm/4h 1880.00000000 ppmV/4h 0.99 mg/l (Exposure time: 1 h) 356 ppm/4h 356.0000000 ppmV/4h			
Pentane (109-66-0)LD50 dermal rabbitLC50 inhalation rat (mg/l)LC50 inhalation rat (ppm)ATE US (dermal)ATE US (gases)ATE US (vapors)ATE US (dust, mist)Carbon monoxide (630-08-0)LC50 inhalation rat (ppm)ATE US (gases)Hydrogen sulfide (7783-06-4)LC50 inhalation rat (mg/l)LC50 inhalation rat (ppm)ATE US (gases)Hydrogen sulfide (7783-06-4)LC50 inhalation rat (ppm)ATE US (gases)ATE US (gases)ATE US (dust, mist)ATE US (dust, mist)ATE US (dust, mist)Nitrogen (7727-37-9)	3000 mg/kg 364 g/m³ (Exposure time: 4 h) 123390 ppm/4h 3000.00000000 mg/kg body weight 123390.00000000 ppmV/4h 364.00000000 mg/l/4h 364.00000000 mg/l/4h 1880 ppm/4h 1880.00000000 ppmV/4h 0.99 mg/l (Exposure time: 1 h) 356 ppm/4h 356.0000000 ppmV/4h			
Pentane (109-66-0) LD50 dermal rabbit LC50 inhalation rat (mg/l) LC50 inhalation rat (ppm) ATE US (dermal) ATE US (gases) ATE US (gases) ATE US (dust, mist) Carbon monoxide (630-08-0) LC50 inhalation rat (ppm) ATE US (gases) Hydrogen sulfide (7783-06-4) LC50 inhalation rat (mg/l) LC50 inhalation rat (ppm) ATE US (gases) ATE US (gases) ATE US (gases) ATE US (gases) ATE US (vapors) ATE US (dust, mist)	3000 mg/kg 364 g/m³ (Exposure time: 4 h) 123390 ppm/4h 3000.0000000 mg/kg body weight 123390.0000000 ppmV/4h 364.0000000 mg/l/4h 364.0000000 mg/l/4h 1880 ppm/4h 1880.0000000 ppmV/4h 0.99 mg/l (Exposure time: 1 h) 356 ppm/4h 356.0000000 ppmV/4h 0.9900000 mg/l/4h			
Pentane (109-66-0)LD50 dermal rabbitLC50 inhalation rat (mg/l)LC50 inhalation rat (ppm)ATE US (dermal)ATE US (gases)ATE US (vapors)ATE US (dust, mist)Carbon monoxide (630-08-0)LC50 inhalation rat (ppm)ATE US (gases)Hydrogen sulfide (7783-06-4)LC50 inhalation rat (mg/l)LC50 inhalation rat (ppm)ATE US (gases)Hydrogen sulfide (7783-06-4)LC50 inhalation rat (mg/l)LC50 inhalation rat (ppm)ATE US (gases)ATE US (gases)ATE US (ust, mist)Nitrogen (7727-37-9)LC50 inhalation rat (ppm)	3000 mg/kg 364 g/m³ (Exposure time: 4 h) 123390 ppm/4h 3000.0000000 mg/kg body weight 123390.0000000 ppmV/4h 364.0000000 mg/l/4h 364.0000000 mg/l/4h 1880 ppm/4h 1880.0000000 ppmV/4h 0.99 mg/l (Exposure time: 1 h) 356 ppm/4h 356.0000000 ppmV/4h 0.99 mg/l (Exposure time: 1 h) 356.0000000 ppmV/4h 0.9900000 mg/l/4h 0.9900000 mg/l/4h 410000 ppm/4h			

pH: Not applicable for gas-mixtures. Respiratory or skin sensitization : Not classified

EN (English US)

Carcinogenicity

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated	: Not classified
exposure)	No known effects from this product.
Aspiration hazard	: Not classified
	Not applicable for gases and gas-mixtures.
Symptoms/injuries after inhalation	: Adverse effects not expected from this product.
Symptoms/injuries after skin contact	: Adverse effects not expected from this product.
Symptoms/injuries after eye contact	: Adverse effects not expected from this product.
Symptoms/injuries after ingestion	: Ingestion is not considered a potential route of exposure.
Symptoms/injuries upon intravenous administration	: Not known.
Chronic symptoms	: Adverse effects not expected from this product.
SECTION 12: Ecological information	1
12.1. Toxicity	
Ecology - general	: No ecological damage caused by this product.
Pentane (109-66-0)	
LCEO fish 1	0.97 mg// (Evenerus times 06 h. Species Operative by mylice)

LC50 fish 1	9.87 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	9.74 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	11.59 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
Hydrogen sulfide (7783-06-4)	
LC50 fish 1	0.0448 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through])
EC50 Daphnia 1	0.022 mg/l (Exposure time: 96 h - Species: Gammarus pseudolimnaeus)
LC50 fish 2	0.016 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])

12.2. Persistence and degradability

Oxygen (15 - 23.5%,) Pentane (0 - 0.75%,) Carbon Monoxide (0.0005-0.09%,) Hydrogen Sulfide (0.001-0.025%) in balance Nitrogen			
Persistence and degradability	No data available.		
Oxygen (7782-44-7)			
Persistence and degradability	No ecological damage caused by this product.		
Carbon monoxide (630-08-0)			
Persistence and degradability	Will not undergo hydrolysis. Not readily biodegradable. Not applicable for inorganic gases.		
Hydrogen sulfide (7783-06-4)			
Persistence and degradability	Not applicable for inorganic gases.		
Nitrogen (7727-37-9)			
Persistence and degradability	No ecological damage caused by this product.		

12.3. **Bioaccumulative potential**

Oxygen (15 - 23.5%,) Pentane (0 - 0.	75%,) Carbon Monoxide (0.0005-0.09%,)	Hydrogen Sulfide (0.001-0.025%) in balance	e Nitrogen
Log Pow	Not applicable for gas-mixtures	5.	
Log Kow	Not applicable for gas-mixture	S.	
Bioaccumulative potential	No data available.	No data available.	
Oxygen (7782-44-7)			
Log Pow	Not applicable for inorganic ga	ses.	
Bioaccumulative potential	No ecological damage caused	No ecological damage caused by this product.	
Pentane (109-66-0)			
Log Pow	3.39	3.39	
Carbon monoxide (630-08-0)			
Log Pow	1.78		
09/23/2015	EN (English US)	SDS ID: 50213	6

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carbon monoxide (630-08-0)	
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.
Hydrogen sulfide (7783-06-4)	
BCF fish 1	(no bioaccumulation expected)
Log Pow	Not applicable for inorganic gases.
Bioaccumulative potential	No data available.
Nitrogen (7727-37-9)	
Log Pow	Not applicable for inorganic gases.
Bioaccumulative potential	No ecological damage caused by this product.
2.4. Mobility in soil	
Oxygen (15 - 23.5%,) Pentane (0 - 0.75%,) Car	bon Monoxide (0.0005-0.09%,) Hydrogen Sulfide (0.001-0.025%) in balance Nitrogen
Mobility in soil	No data available.
Oxygen (7782-44-7)	
Ecology - soil	No ecological damage caused by this product.
Carbon monoxide (630-08-0)	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.
Hydrogen sulfide (7783-06-4)	Peopueo of its high valatility, the product is uplikely to source proved as writer all stick
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.
Nitrogen (7727-37-9)	
Ecology - soil	No ecological damage caused by this product.
2.5. Other adverse effects	
	: None.
iffect on ozone layer	: Contains greenhouse gas(es) not covered by 842/2006/EC.
Effect on ozone layer Effect on the global warming SECTION 13: Disposal consideration	: Contains greenhouse gas(es) not covered by 842/2006/EC.
Effect on ozone layer Effect on the global warming SECTION 13: Disposal consideration 13.1. Waste treatment methods	 Contains greenhouse gas(es) not covered by 842/2006/EC. Contact supplier if guidance is required. May be vented to atmosphere. Do not discharge into
Effect on ozone layer Effect on the global warming SECTION 13: Disposal consideration	 Contains greenhouse gas(es) not covered by 842/2006/EC. Contact supplier if guidance is required. May be vented to atmosphere. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local stress of the stres
Effect on ozone layer Effect on the global warming SECTION 13: Disposal consideration 13.1. Waste treatment methods Waste treatment methods	 Contains greenhouse gas(es) not covered by 842/2006/EC. Contact supplier if guidance is required. May be vented to atmosphere. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from loca regulations or operating permits are not exceeded.
Effect on ozone layer Effect on the global warming SECTION 13: Disposal consideration 3.1. Waste treatment methods Vaste treatment methods	 Contains greenhouse gas(es) not covered by 842/2006/EC. Contact supplier if guidance is required. May be vented to atmosphere. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local stress of the stres
Effect on ozone layer Effect on the global warming SECTION 13: Disposal consideration 3.1. Waste treatment methods Vaste treatment methods Waste disposal recommendations	 Contains greenhouse gas(es) not covered by 842/2006/EC. Contact supplier if guidance is required. May be vented to atmosphere. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from loca regulations or operating permits are not exceeded. Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more
Effect on ozone layer Effect on the global warming SECTION 13: Disposal consideration (3.1. Waste treatment methods Waste treatment methods Waste disposal recommendations SECTION 14: Transport information	 Contains greenhouse gas(es) not covered by 842/2006/EC. Contact supplier if guidance is required. May be vented to atmosphere. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from loca regulations or operating permits are not exceeded. Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more
Effect on ozone layer Effect on the global warming EECTION 13: Disposal consideration 3.1. Waste treatment methods Waste treatment methods Waste disposal recommendations EECTION 14: Transport information n accordance with DOT	 Contains greenhouse gas(es) not covered by 842/2006/EC. Contact supplier if guidance is required. May be vented to atmosphere. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from loca regulations or operating permits are not exceeded. Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more guidance on suitable disposal methods.
Effect on ozone layer Effect on the global warming SECTION 13: Disposal consideration 3.1. Waste treatment methods Vaste treatment methods Waste disposal recommendations SECTION 14: Transport information In accordance with DOT Transport document description	 Contains greenhouse gas(es) not covered by 842/2006/EC. Contact supplier if guidance is required. May be vented to atmosphere. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from loca regulations or operating permits are not exceeded. Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more
Effect on ozone layer Effect on the global warming SECTION 13: Disposal consideration 3.1. Waste treatment methods Vaste treatment methods Waste disposal recommendations SECTION 14: Transport information In accordance with DOT Transport document description JN-No.(DOT)	 Contains greenhouse gas(es) not covered by 842/2006/EC. Contact supplier if guidance is required. May be vented to atmosphere. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from loca regulations or operating permits are not exceeded. Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more guidance on suitable disposal methods. UN1956 Compressed gas, n.o.s. (Oxygen, Nitrogen)
Effect on ozone layer Effect on the global warming SECTION 13: Disposal consideration 3.1. Waste treatment methods Vaste treatment methods Waste disposal recommendations SECTION 14: Transport information In accordance with DOT Transport document description JN-No.(DOT) DOT NA no.	 Contains greenhouse gas(es) not covered by 842/2006/EC. Contact supplier if guidance is required. May be vented to atmosphere. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from loca regulations or operating permits are not exceeded. Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more guidance on suitable disposal methods. UN1956 Compressed gas, n.o.s. (Oxygen, Nitrogen) 1956
Effect on ozone layer Effect on the global warming SECTION 13: Disposal consideration 13.1. Waste treatment methods Waste treatment methods Waste disposal recommendations SECTION 14: Transport information n accordance with DOT Transport document description JN-No.(DOT) DOT NA no.	 Contains greenhouse gas(es) not covered by 842/2006/EC. Contact supplier if guidance is required. May be vented to atmosphere. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from loca regulations or operating permits are not exceeded. Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more guidance on suitable disposal methods. UN1956 Compressed gas, n.o.s. (Oxygen, Nitrogen) 1956 UN1956
Effect on ozone layer Effect on the global warming SECTION 13: Disposal consideration 13.1. Waste treatment methods Waste treatment methods Waste disposal recommendations SECTION 14: Transport information n accordance with DOT Fransport document description JN-No.(DOT) DOT NA no. DOT Proper Shipping Name	 Contains greenhouse gas(es) not covered by 842/2006/EC. Contact supplier if guidance is required. May be vented to atmosphere. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local regulations or operating permits are not exceeded. Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more guidance on suitable disposal methods. UN1956 Compressed gas, n.o.s. (Oxygen, Nitrogen) 1956 UN1956 Compressed gas, n.o.s.
Effect on ozone layer Effect on the global warming SECTION 13: Disposal consideration 13.1. Waste treatment methods	 Contains greenhouse gas(es) not covered by 842/2006/EC. Contact supplier if guidance is required. May be vented to atmosphere. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from locar regulations or operating permits are not exceeded. Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more guidance on suitable disposal methods. UN1956 Compressed gas, n.o.s. (Oxygen, Nitrogen) 1956 UN1956 Compressed gas, n.o.s. (Oxygen, Nitrogen) N1956 Compressed gas, n.o.s. (Oxygen, Nitrogen)
Effect on ozone layer Effect on the global warming SECTION 13: Disposal consideration 13.1. Waste treatment methods Waste treatment methods Waste disposal recommendations SECTION 14: Transport information n accordance with DOT Fransport document description JN-No.(DOT) DOT NA no. DOT Proper Shipping Name	 Contains greenhouse gas(es) not covered by 842/2006/EC. Contact supplier if guidance is required. May be vented to atmosphere. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from loca regulations or operating permits are not exceeded. Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more guidance on suitable disposal methods. UN1956 Compressed gas, n.o.s. (Oxygen, Nitrogen) 1956 UN1956 Compressed gas, n.o.s. (Oxygen, Nitrogen) N1956 Compressed gas, n.o.s. (Oxygen, Nitrogen)
Effect on ozone layer Effect on the global warming SECTION 13: Disposal consideration 13.1. Waste treatment methods Waste treatment methods Waste disposal recommendations SECTION 14: Transport information n accordance with DOT Fransport document description JN-No.(DOT) DOT NA no. DOT Proper Shipping Name	 Contains greenhouse gas(es) not covered by 842/2006/EC. Contact supplier if guidance is required. May be vented to atmosphere. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from loca regulations or operating permits are not exceeded. Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more guidance on suitable disposal methods. UN1956 Compressed gas, n.o.s. (Oxygen, Nitrogen) 1956 UN1956 Compressed gas, n.o.s. (Oxygen, Nitrogen) N1956 Compressed gas, n.o.s. (Oxygen, Nitrogen)
Effect on ozone layer Effect on the global warming SECTION 13: Disposal consideration I3.1. Waste treatment methods Waste treatment methods Waste disposal recommendations SECTION 14: Transport information n accordance with DOT Fransport document description JN-No.(DOT) DOT NA no. DOT Proper Shipping Name	 Contains greenhouse gas(es) not covered by 842/2006/EC. Contact supplier if guidance is required. May be vented to atmosphere. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from loca regulations or operating permits are not exceeded. Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more guidance on suitable disposal methods. UN1956 Compressed gas, n.o.s. (Oxygen, Nitrogen) 1956 UN1956 Compressed gas, n.o.s. (Oxygen, Nitrogen) N1956 Compressed gas, n.o.s. (Oxygen, Nitrogen)
Effect on ozone layer Effect on the global warming SECTION 13: Disposal consideration 13.1. Waste treatment methods Waste treatment methods Waste disposal recommendations SECTION 14: Transport information In accordance with DOT Fransport document description JN-No. (DOT) DOT NA no. DOT Proper Shipping Name Hazard labels (DOT)	 Contains greenhouse gas(es) not covered by 842/2006/EC. Contact supplier if guidance is required. May be vented to atmosphere. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from loca regulations or operating permits are not exceeded. Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more guidance on suitable disposal methods. UN1956 Compressed gas, n.o.s. (Oxygen, Nitrogen) 1956 UN1956 Compressed gas, n.o.s. (Oxygen, Nitrogen) 2.2 - Non-flammable gas
Effect on ozone layer Effect on the global warming SECTION 13: Disposal consideration 13.1. Waste treatment methods Waste treatment methods Waste disposal recommendations SECTION 14: Transport information In accordance with DOT Transport document description JN-No. (DOT) DOT NA no. DOT Proper Shipping Name Hazard labels (DOT)	 Contains greenhouse gas(es) not covered by 842/2006/EC. Contact supplier if guidance is required. May be vented to atmosphere. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from loca regulations or operating permits are not exceeded. Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more guidance on suitable disposal methods. UN1956 Compressed gas, n.o.s. (Oxygen, Nitrogen) 1956 UN1956 Compressed gas, n.o.s. (Oxygen, Nitrogen) N1956 Compressed gas, n.o.s. (Oxygen, Nitrogen)
Effect on ozone layer Effect on the global warming SECTION 13: Disposal consideration I3.1. Waste treatment methods Waste treatment methods Waste disposal recommendations SECTION 14: Transport information n accordance with DOT Fransport document description JN-No.(DOT) DOT NA no. DOT Proper Shipping Name	 Contains greenhouse gas(es) not covered by 842/2006/EC. Contact supplier if guidance is required. May be vented to atmosphere. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from locar regulations or operating permits are not exceeded. Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more guidance on suitable disposal methods. UN1956 Compressed gas, n.o.s. (Oxygen, Nitrogen) 1956 UN1956 Compressed gas, n.o.s. (Oxygen, Nitrogen) 2.2 - Non-flammable gas G - Identifies PSN requiring a technical name
Effect on ozone layer Effect on the global warming SECTION 13: Disposal consideration 13.1. Waste treatment methods Waste treatment methods Waste disposal recommendations SECTION 14: Transport information n accordance with DOT Transport document description JN-No. (DOT) DOT NA no. DOT Proper Shipping Name Hazard labels (DOT)	 Contains greenhouse gas(es) not covered by 842/2006/EC. Contact supplier if guidance is required. May be vented to atmosphere. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from loca regulations or operating permits are not exceeded. Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more guidance on suitable disposal methods. UN1956 Compressed gas, n.o.s. (Oxygen, Nitrogen) 1956 UN1956 Compressed gas, n.o.s. (Oxygen, Nitrogen) 2.2 - Non-flammable gas G - Identifies PSN requiring a technical name 306;307
Effect on ozone layer Effect on the global warming SECTION 13: Disposal consideration 3.1. Waste treatment methods Vaste treatment methods Waste disposal recommendations SECTION 14: Transport information In accordance with DOT Transport document description JN-No.(DOT) DOT NA no. DOT Proper Shipping Name Hazard labels (DOT) DOT Symbols DOT Symbols DOT Packaging Exceptions (49 CFR 173.xxx) DOT Packaging Non Bulk (49 CFR 173.xxx)	 Contains greenhouse gas(es) not covered by 842/2006/EC. Contact supplier if guidance is required. May be vented to atmosphere. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local regulations or operating permits are not exceeded. Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more guidance on suitable disposal methods. UN1956 Compressed gas, n.o.s. (Oxygen, Nitrogen) 1956 UN1956 Compressed gas, n.o.s. (Oxygen, Nitrogen) 2.2 - Non-flammable gas G - Identifies PSN requiring a technical name 306;307 302;305

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

,	
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Additional information	
Other information	: No supplementary information available.
Special transport precautions	: Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: - Ensure there is adequate ventilation Ensure that containers are firmly secured Ensure cylinder valve is closed and not leaking Ensure valve outlet cap nut or plug (where provided) is correctly fitted Ensure valve protection device (where provided) is correctly fitted.
ADR	
Fransport document description	:
Transport by sea	4050
JN-No. (IMDG)	
Proper Shipping Name (IMDG)	: COMPRESSED GAS, N.O.S.
Class (IMDG)	: 2.2 - Non-flammable, non-toxic gases
Air transport	
JN-No.(IATA)	: 1956
Proper Shipping Name (IATA)	: COMPRESSED GAS, N.O.S.
Class (IATA)	: 2
· ·	
SECTION 15: Regulatory information	
15.1. US Federal regulations	
Pentane (109-66-0)	
Listed on the United States TSCA (Toxic Substa	Inces Control Act) inventory
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
Hydrogen sulfide (7783-06-4)	
Listed on the United States TSCA (Toxic Substa Listed on the United States SARA Section 302 Listed on United States SARA Section 313	inces Control Act) inventory
SARA Section 302 Threshold Planning Quantity (TPQ)	500
SARA Section 313 - Emission Reporting	1.0 %
15.2. International regulations	
15.2. International regulations	
Oxygen (7782-44-7)	
Listed on the Canadian DSL (Domestic Sustance WHMIS Classification	es List) Class A - Compressed Gas
	Class C - Oxidizing Material
Pentane (109-66-0)	
Listed on the Canadian DSL (Domestic Sustance	,
WHMIS Classification	Class B Division 2 - Flammable Liquid
Carbon monoxide (630-08-0)	
Listed on the Canadian DSL (Domestic Sustance	es List)
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hydrogen sulfide (7783-06-4)		
Listed on the Canadian DSL (Domestic Sustances List)		
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects	
Nitrogen (7727-37-9)		
Listed on the Canadian DSL (Domestic Sustances List)		
HMIS Classification Class A - Compressed Gas		

EU-Regulations

Hydrogen sulfide (7783-06-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP] Not classified

Classification according to Directive 67/548/EEC or 1999/45/EC

15.2.2. National regulations

Hydrogen sulfide (7783-06-4)

Listed on the AICS (the Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the Canadian IDL (Ingredient Disclosure List)

15.3. US State regulations

Carbon monoxide (630-08-0				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
	Yes			

Oxygen (7782-44-7)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

Pentane (109-66-0)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

Carbon monoxide (630-08-0)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Hydrogen sulfide (7783-06-4)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Nitrogen (7727-37-9)

U.S. - Massachusetts - Right To Know List

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Nitrogen (7727-37-9)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

SECTION 16: Other information Indication of changes : Revised safety data sheet in accordance with OSHA final rule on GHS implementation promulgated March 26, 2012. Revision date

Other information

08/15/2014

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product.

Full text of H-phrases: see section 16:

Acute Tox. 2 (Inhalation:gas)Acute toxicity (inhalation:gas) Category 2Acute Tox. 3 (Inhalation:gas)Acute toxicity (inhalation:gas) Category 3Asp. Tox. 1Aspiration hazard Category 1Compressed gasGases under pressure Compressed gasFlam. Gas 1Flammable gases Category 2Liquefied gasGases under pressure Liquefied gasOx. Gas 1Stategory 1Repr. 1AReproductive toxicity (repeated exposure) Category 1STOT RE 1Specific target organ toxicity (repeated exposure) Category 3STOT SE 3Specific target organ toxicity (single exposure) Category 3H220Extremely flammable gasH225Highly flammable gasH226Highly flammable liquid and vaporH270May cause or intensify fire; oxidizerH280Contains gas under pressure; may explode if heatedH300Fatal if inhaledH331Toxic if inbaled		
Asp. Tox. 1Aspiration hazard Category 1Compressed gasGases under pressure Compressed gasFlam. Gas 1Flammable gases Category 1Flam. Liq. 2Flammable liquids Category 2Liquefied gasGases under pressure Liquefied gasOx. Gas 1Oxidizing gases Category 1Repr. 1AReproductive toxicity Category 1ASTOT RE 1Specific target organ toxicity (repeated exposure) Category 3STOT SE 3Specific target organ toxicity (single exposure) Category 3STOT SE 3Specific target organ toxicity (single exposure) Category 3H220Extremely flammable gasH225Highly flammable liquid and vaporH270May cause or intensify fire; oxidizerH280Contains gas under pressure; may explode if heatedH304May be fatal if swallowed and enters airwaysH330Fatal if inhaled	Acute Tox. 2 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 2
Compressed gasGases under pressure Compressed gasFlam. Gas 1Flammable gases Category 1Flam. Liq. 2Flammable liquids Category 2Liquefied gasGases under pressure Liquefied gasOx. Gas 1Oxidizing gases Category 1Repr. 1AReproductive toxicity Category 1ASTOT RE 1Specific target organ toxicity (repeated exposure) Category 1STOT SE 3Specific target organ toxicity (single exposure) Category 3STOT SE 3Specific target organ toxicity (single exposure) Category 3H220Extremely flammable gasH225Highly flammable liquid and vaporH270May cause or intensify fire; oxidizerH280Contains gas under pressure; may explode if heatedH304May be fatal if swallowed and enters airwaysH330Fatal if inhaled	Acute Tox. 3 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 3
Flam. Gas 1Flammable gases Category 1Flam. Liq. 2Flammable liquids Category 2Liquefied gasGases under pressure Liquefied gasOx. Gas 1Oxidizing gases Category 1Repr. 1AReproductive toxicity Category 1ASTOT RE 1Specific target organ toxicity (repeated exposure) Category 1STOT SE 3Specific target organ toxicity (single exposure) Category 3STOT SE 3Specific target organ toxicity (single exposure) Category 3H220Extremely flammable gasH225Highly flammable liquid and vaporH270May cause or intensify fire; oxidizerH280Contains gas under pressure; may explode if heatedH304May be fatal if swallowed and enters airwaysH330Fatal if inhaled	Asp. Tox. 1	Aspiration hazard Category 1
Flam. Liq. 2Flammable liquids Category 2Liquefied gasGases under pressure Liquefied gasOx. Gas 1Oxidizing gases Category 1Repr. 1AReproductive toxicity Category 1ASTOT RE 1Specific target organ toxicity (repeated exposure) Category 1STOT SE 3Specific target organ toxicity (single exposure) Category 3STOT SE 3Specific target organ toxicity (single exposure) Category 3H220Extremely flammable gasH225Highly flammable liquid and vaporH270May cause or intensify fire; oxidizerH280Contains gas under pressure; may explode if heatedH304May be fatal if swallowed and enters airwaysH330Fatal if inhaled	Compressed gas	Gases under pressure Compressed gas
Liquefied gasGases under pressure Liquefied gasOx. Gas 1Oxidizing gases Category 1Repr. 1AReproductive toxicity Category 1ASTOT RE 1Specific target organ toxicity (repeated exposure) Category 1STOT SE 3Specific target organ toxicity (single exposure) Category 3STOT SE 3Specific target organ toxicity (single exposure) Category 3H220Extremely flammable gasH225Highly flammable liquid and vaporH270May cause or intensify fire; oxidizerH280Contains gas under pressure; may explode if heatedH304May be fatal if swallowed and enters airwaysH330Fatal if inhaled	Flam. Gas 1	Flammable gases Category 1
Ox. Gas 1Oxidizing gases Category 1Repr. 1AReproductive toxicity Category 1ASTOT RE 1Specific target organ toxicity (repeated exposure) Category 1STOT SE 3Specific target organ toxicity (single exposure) Category 3STOT SE 3Specific target organ toxicity (single exposure) Category 3H220Extremely flammable gasH225Highly flammable liquid and vaporH270May cause or intensify fire; oxidizerH280Contains gas under pressure; may explode if heatedH304May be fatal if swallowed and enters airwaysH330Fatal if inhaled	Flam. Liq. 2	Flammable liquids Category 2
Repr. 1AReproductive toxicity Category 1ASTOT RE 1Specific target organ toxicity (repeated exposure) Category 1STOT SE 3Specific target organ toxicity (single exposure) Category 3STOT SE 3Specific target organ toxicity (single exposure) Category 3H220Extremely flammable gasH225Highly flammable liquid and vaporH270May cause or intensify fire; oxidizerH280Contains gas under pressure; may explode if heatedH304May be fatal if swallowed and enters airwaysH330Fatal if inhaled	Liquefied gas	Gases under pressure Liquefied gas
STOT RE 1Specific target organ toxicity (repeated exposure) Category 1STOT SE 3Specific target organ toxicity (single exposure) Category 3STOT SE 3Specific target organ toxicity (single exposure) Category 3H220Extremely flammable gasH225Highly flammable liquid and vaporH270May cause or intensify fire; oxidizerH280Contains gas under pressure; may explode if heatedH304May be fatal if swallowed and enters airwaysH330Fatal if inhaled	Ox. Gas 1	Oxidizing gases Category 1
STOT SE 3Specific target organ toxicity (single exposure) Category 3STOT SE 3Specific target organ toxicity (single exposure) Category 3H220Extremely flammable gasH225Highly flammable liquid and vaporH270May cause or intensify fire; oxidizerH280Contains gas under pressure; may explode if heatedH304May be fatal if swallowed and enters airwaysH330Fatal if inhaled	Repr. 1A	Reproductive toxicity Category 1A
STOT SE 3Specific target organ toxicity (single exposure) Category 3H220Extremely flammable gasH225Highly flammable liquid and vaporH270May cause or intensify fire; oxidizerH280Contains gas under pressure; may explode if heatedH304May be fatal if swallowed and enters airwaysH330Fatal if inhaled	STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
H220Extremely flammable gasH225Highly flammable liquid and vaporH270May cause or intensify fire; oxidizerH280Contains gas under pressure; may explode if heatedH304May be fatal if swallowed and enters airwaysH330Fatal if inhaled	STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225Highly flammable liquid and vaporH270May cause or intensify fire; oxidizerH280Contains gas under pressure; may explode if heatedH304May be fatal if swallowed and enters airwaysH330Fatal if inhaled	STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H270May cause or intensify fire; oxidizerH280Contains gas under pressure; may explode if heatedH304May be fatal if swallowed and enters airwaysH330Fatal if inhaled	H220	Extremely flammable gas
H280Contains gas under pressure; may explode if heatedH304May be fatal if swallowed and enters airwaysH330Fatal if inhaled	H225	Highly flammable liquid and vapor
H304 May be fatal if swallowed and enters airways H330 Fatal if inhaled	H270	May cause or intensify fire; oxidizer
H330 Fatal if inhaled	H280	Contains gas under pressure; may explode if heated
	H304	May be fatal if swallowed and enters airways
H331 Toxic if inhaled	H330	Fatal if inhaled
	H331	Toxic if inhaled
H335 May cause respiratory irritation	H335	May cause respiratory irritation
H336 May cause drowsiness or dizziness	H336	May cause drowsiness or dizziness
H360 May damage fertility or the unborn child	H360	May damage fertility or the unborn child
H372 Causes damage to organs through prolonged or repeated expo	H372	Causes damage to organs through prolonged or repeated exposure

SDS US (GHS HazCom 2012)

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this gas mixture. To the best of Calgaz's knowledge, the information contained herein is reliable and accurate as of this date; however, accruacy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this gas mixture is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.