

## Safety Data Sheet PTG-4026

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 05/25/2015 Version: 1.0

## SECTION: 1. Product and company identification

1.1. Product identifier

Product form : Mixture

Formula : Non-flammable, Non-oxidizing gas mixture containing one or more of the following

components: R-507, R-502, R-500, Oxygen, Nitrogen.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Calibration / Reference
Use of the substance/mixture : Industrial use. Use as directed.

1.3. Details of the supplier of the safety data sheet

Manufactured For: By:

Mine Safety Appliances Company, Ilc.

1000 Cranberry Woods Drive

Cranberry Township, PA 16066

Phone: 724-776-8600

PortaGas(Praxair,Inc)

1202 E Sam Houston Pkwy S

Pasadena, TX 77503

713-928-6477

Phone: 724-776-8600 Info.us@msasafety.com

1.4. Emergency telephone number

Emergency number : Onsite Emergencies: 1-800-645-4633

CHEMTREC: USA 1-800-424-9300, International 001-703-527-3887 (Collect calls accepted,

contract 17729)

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

#### **Classification (GHS-US)**

Compressed gas H280

### 2.2. Label elements

### **GHS-US** labeling

Hazard pictograms (GHS-US)



GHS04

Signal word (GHS-US) : WARNING

Hazard statements (GHS-US) : H280 - CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED

Precautionary statements (GHS-US) : P410+P403 - Protect from sunlight when ambient temperature exceeds 52°C (125°F). Use and

store only outdoors or in a well-ventilated place.

CGA-PG27 - Read and follow the Safety Data Sheet (SDS) before use.

CGA-PG21 - Open valve slowly.

CGA-PG10 - Use only with equipment rated for cylinder pressure.

CGA-PG12 - Do not open valve until connected to equipment prepared for use. CGA-PG11 - Never put cylinders into unventilated areas of passenger vehicles.

CGA-PG06 - Close valve after each use and when empty. CGA-PG05 - Use a back flow preventive device in the piping.

CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F).

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

EN (English US) SDS ID: PTG-4026 1/9



## Safety Data Sheet PTG-4026

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 05/25/2015 Version: 1.0

### **SECTION 3: Composition/information on ingredients**

#### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%
Nitrogen	(CAS No) 7727-37-9	79.1 - 99.999
Oxygen	(CAS No) 7782-44-7	0.0001 - 20.9
1,1,1-Trifluoroethane	(CAS No) 420-46-2	0.00005 - 0.5
Pentafluoroethane	(CAS No) 354-33-6	0.00005 - 0.5
Ethane, chloropentafluoro-, mixture with chlorodifluoromethane	(CAS No) 39432-81-0	0.0001 - 0.01
Ethane, 1,1-difluoro-, mixture with dichlorodifluoromethane	(CAS No) 56275-41-3	0.0001 - 0.01

### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

First-aid measures after inhalation : Immediately remove to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, qualified personnel may give oxygen. Call a physician.

First-aid measures after skin contact : Adverse effects not expected from this product.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Hold the eyelids open and

away from the eyeballs to ensure that all surfaces are flushed thoroughly. Contact an

ophthalmologist immediately.

First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

#### 4.2. Most important symptoms and effects, both acute and delayed

No additional information available

### 4.3. Indication of any immediate medical attention and special treatment needed

None.

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

#### 5.2. Special hazards arising from the substance or mixture

Reactivity : No reactivity hazard other than the effects described in sub-sections below.

### 5.3. Advice for firefighters

Firefighting instructions : Evacuate all personnel from the danger area. Use self-contained breathing apparatus (SCBA)

and protective clothing. Immediately cool containers with water from maximum distance. Stop flow of gas if safe to do so, while continuing cooling water spray. Remove ignition sources if safe to do so. Remove containers from area of fire if safe to do so. On-site fire brigades must comply with OSHA 29 CFR 1910.156 and applicable standards under 29 CFR 1910 Subpart

L-Fire Protection.

Special protective equipment for fire fighters : Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire

fighters.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

### 6.1.1. For non-emergency personnel

No additional information available

### 6.1.2. For emergency responders

No additional information available

### 6.2. Environmental precautions

Prevent waste from contaminating the surrounding environment. Prevent soil and water pollution. Dispose of contents/container in accordance with local/regional/national/international regulations. Contact supplier for any special requirements.

EN (English US) SDS ID: PTG-4026 2/9



## Safety Data Sheet PTG-4026

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 05/25/2015 Version: 1.0

### 6.3. Methods and material for containment and cleaning up

No additional information available

### 6.4. Reference to other sections

See also sections 8 and 13.

### **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Precautions for safe handling

: Wear leather safety gloves and safety shoes when handling cylinders. Protect cylinders from physical damage; do not drag, roll, slide or drop. While moving cylinder, always keep in place removable valve cover. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Never insert an object (e.g., wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Slowly open the valve. If the valve is hard to open, discontinue use and contact your supplier. Close the container valve after each use; keep closed even when empty. Never apply flame or localized heat directly to any part of the container. High temperatures may damage the container and could cause the pressure relief device to fail prematurely, venting the container contents. For other precautions in using this product, see section 16.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store in a cool, well-ventilated place. Store and use with adequate ventilation. Store only where temperature will not exceed 125°F (52°C). Firmly secure containers upright to keep them from falling or being knocked over. Install valve protection cap, if provided, firmly in place by hand. Store full and empty containers separately. Use a first-in, first-out inventory system to prevent storing full containers for long periods.

OTHER PRECAUTIONS FOR HANDLING, STORAGE, AND USE: When handling product under pressure, use piping and equipment adequately designed to withstand the pressures to be encountered. Never work on a pressurized system. Use a back flow preventive device in the piping. Gases can cause rapid suffocation because of oxygen deficiency; store and use with adequate ventilation. If a leak occurs, close the container valve and blow down the system in a safe and environmentally correct manner in compliance with all international, federal/national, state/provincial, and local laws; then repair the leak. Never place a container where it may become part of an electrical circuit.

### 7.3. Specific end use(s)

None.

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

1,1,1-Trifluoroethane (420-46-2)		
ACGIH	Not established	
USA OSHA	Not established	
Pentafluoroethane (354-33-6		
ACGIH	Not established	
USA OSHA	Not established	
Oxygen (7782-44-7)		
ACGIH	Not established	
USA OSHA	Not established	
Nitrogen (7727-37-9)		
ACGIH	Not established	
USA OSHA	Not established	

EN (English US) SDS ID: PTG-4026 3/9



## Safety Data Sheet PTG-4026

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 05/25/2015 Version: 1.0

### 8.2. Exposure controls

Respiratory protection

Appropriate engineering controls : Provide adequate general and local exhaust ventilation. Ensure exposure is below occupational

exposure limits (where available).

Personal protective equipment : Gloves. Safety glasses.





Eye protection : Wear safety glasses when handling cylinders; vapor-proof goggles and a face shield during

cylinder changeout or whenever contact with product is possible. Select eye protection in

accordance with OSHA 29 CFR 1910.133.

Skin and body protection : Wear metatarsal shoes and work gloves for cylinder handling, and protective clothing where

needed. Wear appropriate chemical gloves during cylinder changeout or wherever contact with

product is possible. Select per OSHA 29 CFR 1910.132, 1910.136, and 1910.138.

When workplace conditions warrant respirator use, follow a respiratory protection program that meets OSHA 29 CFR 1910.134, ANSI Z88.2, or MSHA 30 CFR 72.710 (where applicable). Use an air-supplied or air-purifying cartridge if the action level is exceeded. Ensure that the respirator has the appropriate protection factor for the exposure level. If cartridge type respirators are used, the cartridge must be appropriate for the chemical exposure (e.g., an organic vapor cartridge). For emergencies or instances with unknown exposure levels, use a self-contained breathing apparatus (SCBA) or

positive pressure airline with mask are to be used in oxygen-deficient atmospheres.

Thermal hazard protection : Wear cold insulating gloves when transfilling or breaking transfer connections.

## **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state : Gas
Color : Colorless

Odor : No data available Odor threshold : No data available pΗ Not applicable. Relative evaporation rate (butyl acetate=1) : No data available Relative evaporation rate (ether=1) Not applicable. Melting point : No data available : No data available Freezing point No data available Boiling point Flash point : No data available Auto-ignition temperature No data available Decomposition temperature : No data available : No data available Flammability (solid, gas) Vapor pressure Not applicable. Relative vapor density at 20 °C : No data available Relative density No data available

Solubility : Water: No data available

Log Pow: Not applicable.Log Kow: Not applicable.Viscosity, kinematic: Not applicable.Viscosity, dynamic: Not applicable.Explosive properties: Not applicable.

Oxidizing properties : None.

Explosion limits : No data available



## Safety Data Sheet PTG-4026

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 05/25/2015 Version: 1.0

9.2. Other information

No additional information available

SECT	ION 10: Stability and reactivity	
10.1.	Reactivity	
		No reactivity hazard other than the effects described in sub-sections below.
10.2.	Chemical stability	
		Stable under normal conditions.
10.3.	Possibility of hazardous reactions	
		None.
10.4.	Conditions to avoid	

None.

10.5. Incompatible materials

None.

10.6. **Hazardous decomposition products** 

None.

## **SECTION 11: Toxicological information**

### Information on toxicological effects

: Not classified Acute toxicity

1,1,1-Trifluoroethane (420-46-2)	
LC50 inhalation rat (mg/l)	> 54 lb/h (Exposure time: 4 h)

Skin corrosion/irritation : Not classified

pH: Not applicable.

: Not classified Serious eye damage/irritation

pH: Not applicable.

Respiratory or skin sensitization : Not classified Germ cell mutagenicity Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified Specific target organ toxicity (single exposure) : Not classified Specific target organ toxicity (repeated : Not classified exposure)

: Not classified Aspiration hazard

## **SECTION 12: Ecological information**

12.1. **Toxicity** 

: No known ecological damage caused by this product. Ecology - general

#### Persistence and degradability 12.2.

PTG-4026		
Persistence and degradability  No ecological damage caused by this product.		
1,1,1-Trifluoroethane (420-46-2)		
Persistence and degradability  Not readily biodegradable.		
Oxygen (7782-44-7)		
Persistence and degradability	No ecological damage caused by this product.	

EN (English US) SDS ID: PTG-4026 5/9



## Safety Data Sheet PTG-4026

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 05/25/2015 Version: 1.0

Nitrogen (7727-37-9)	
Persistence and degradability	No ecological damage caused by this product.

### 12.3. Bioaccumulative potential

12.5. Bioaccamalative potential			
PTG-4026			
Log Pow	Not applicable.		
Log Kow	Not applicable.		
Bioaccumulative potential	No ecological damage caused by this product.		
1,1,1-Trifluoroethane (420-46-2)			
Log Pow	Not known.		
Bioaccumulative potential	No data available.		
Oxygen (7782-44-7)			
Log Pow	Not applicable.		
Log Kow	Not applicable.		
Bioaccumulative potential	No ecological damage caused by this product.		
Nitrogen (7727-37-9)			
Log Pow	Not applicable.		
Log Kow	Not applicable.		
Bioaccumulative potential	No ecological damage caused by this product.		

### 12.4. Mobility in soil

12.4. Mobility III Joli		
PTG-4026		
Mobility in soil	No data available.	
1,1,1-Trifluoroethane (420-46-2)		
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.	
Oxygen (7782-44-7)		
Mobility in soil	No data available.	
Ecology - soil	No ecological damage caused by this product.	
Nitrogen (7727-37-9)		
Mobility in soil	No data available.	
Ecology - soil	No ecological damage caused by this product.	

### 12.5. Other adverse effects

Effect on ozone layer : None.

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Waste disposal recommendations : Do not attempt to dispose of residual or unused quantities. Return container to supplier.

## **SECTION 14: Transport information**

In accordance with DOT

Transport document description : UN1956 Compressed gas, n.o.s., 2.2

UN-No.(DOT) : UN1956

Proper Shipping Name (DOT) : Compressed gas, n.o.s.

Transport hazard class(es) (DOT) : 2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115

Hazard labels (DOT) : 2.2 - Non-flammable gas



DOT Symbols : G - Identifies proper shipping name (PSN) requiring the addition of technical name(s) in

parentheses following the PSN.

EN (English US) SDS ID: PTG-4026 6/9



## Safety Data Sheet PTG-4026

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 05/25/2015 Version: 1.0

### **Additional information**

Emergency Response Guide (ERG) Number : 126

Other information : No supplementary information available.

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's

compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers:
- Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure cylinder valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided) is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.

### Transport by sea

UN-No. (IMDG) : 1956

Proper Shipping Name (IMDG) : COMPRESSED GAS, N.O.S.

Class (IMDG) : 2.2 - Non-flammable, non-toxic gases

 Limited quantities (IMDG)
 : 120ml

 EmS-No. (1)
 : F-C

 MFAG-No
 : 620

 EmS-No. (2)
 : S-V

Air transport

UN-No.(IATA) : 1956

Proper Shipping Name (IATA) : COMPRESSED GAS, N.O.S.

Class (IATA) : 2
Instruction "cargo" (ICAO) : 200
Instruction "passenger" (ICAO) : 200

Instruction "passenger" - Limited quantities : FORBIDDEN

(ICAO)

## **SECTION 15: Regulatory information**

### 15.1. US Federal regulations

No additional information available

### 15.2. International regulations

#### **CANADA**

### 1,1,1-Trifluoroethane (420-46-2)

Listed on the Canadian DSL (Domestic Substances List)

## Pentafluoroethane (354-33-6)

Listed on the Canadian DSL (Domestic Substances List)

## Oxygen (7782-44-7)

Listed on the Canadian DSL (Domestic Substances List)

### Nitrogen (7727-37-9)

Listed on the Canadian DSL (Domestic Substances List)

## **EU-Regulations**

## 15.2.2. National regulations

No additional information available

EN (English US) SDS ID: PTG-4026 7/9



## Safety Data Sheet PTG-4026

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 05/25/2015 Version: 1.0

15.3. US State regulations PTG-4026()	
U.S California - Proposition 65 - Carcinogens List	No
U.S California - Proposition 65 - Developmental Toxicity	No
U.S California - Proposition 65 - Reproductive Toxicity - Female	No
U.S California - Proposition 65 - Reproductive Toxicity - Male	No

1,1,1-Trifluoroethane (				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk leve (NSRL)
No	No	No	No	
Pentafluoroethane (35	4-33-6)			
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk leve (NSRL)
No	No	No	No	
Ethane, chloropentafle	uoro-, mixture with chlorodifluo	romethane (39432-81-0)		
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	No	No	No	
Ethane, 1,1-difluoro-,	mixture with dichlorodifluorome	ethane (56275-41-3)		
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	No	No	No	
Oxygen (7782-44-7)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	No	No	No	
Nitrogen (7727-37-9)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
	No	No	No	<del> </del>

## Oxygen (7782-44-7)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

## Nitrogen (7727-37-9)

- U.S. Massachusetts Right To Know List U.S. New Jersey Right to Know Hazardous Substance List

EN (English US) SDS ID: PTG-4026 8/9



## Safety Data Sheet PTG-4026

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 05/25/2015 Version: 1.0

### Nitrogen (7727-37-9)

U.S. - Pennsylvania - RTK (Right to Know) List

### **SECTION 16: Other information**

Other information

: When you mix two or more chemicals, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an industrial hygienist or other trained person when you evaluate the end product. Before using any plastics, confirm their compatibility with this product.

Praxair asks users of this product to study this SDS and become aware of the product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this SDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information.

The opinions expressed herein are those of qualified experts within Praxair, Inc. We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and the conditions of use are not within the control of Praxair, Inc., it is the user's obligation to determine the conditions of safe use of the product.

Praxair SDSs are furnished on sale or delivery by Praxair or the independent distributors and suppliers who package and sell our products. To obtain current SDSs for these products, contact your Praxair sales representative, local distributor, or supplier, or download from www.praxair.com. If you have questions regarding Praxair SDSs, would like the document number and date of the latest SDS, or would like the names of the Praxair suppliers in your area, phone or write the Praxair Call Center (Phone: 1-800-PRAXAIR/1-800-772-9247; Address: Praxair Call Center, Praxair, Inc., P.O. Box 44, Tonawanda, NY 14151-0044).

PRAXAIR and the Flowing Airstream design are trademarks or registered trademarks of Praxair Technology, Inc. in the United States and/or other countries.

MSA Part Numbers: 813370, 813371

SDS US (GHS HazCom 2012) - Praxair

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.