

## Safety Data Sheet PTG-4032

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 05/11/2015 Revision date: 07/01/2015 Supersedes: 06/08/2015

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture, MSA Part Number 10172318

Formula : Non-flammable, Non-oxidizing gas mixture containing one or more of the following

components: Hexane, Heptane, Isobutene, Oxygen, Nitrogen.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Calibration / Reference
Use of the substance/mixture : Industrial use. Use as directed.

1.3. Details of the supplier of the safety data sheet

Manufacturer: PortaGas (Praxair, Inc.)

1202 E Sam Houston Pkwy S Pasadena, TX 77503 - USA

T +1 713-928-6477 - F +1 713-928-9961

www.praxair.com

Distributor: MSA Safety Inc.

1000 Cranberry Woods Drive Cranberry Township, PA 16066 -USAPhone: 724-776-8600 Info.us@msasafety.com Version: 1.1

1.4. Emergency telephone number

Emergency number : Onsite Emergencies: 1-800-645-4633

CHEMTREC: USA 1-800-424-9300, International 001-703-527-3887 (Collect calls accepted,

contract 17729)

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

## **Classification (GHS-US)**

Compressed gas H280

Full text of H-phrases: see section 16

### 2.2. Label elements

## **GHS-US** labeling

Hazard pictograms (GHS-US)



GHS04

Signal word (GHS-US) : WARNING

Hazard statements (GHS-US) : H280 - CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED

Precautionary statements (GHS-US) : P403 - Use and store only oudoors or in a well-ventilated place.

CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F). CGA-PG12 - Do not open valve until connected to equipment prepared for use.

CGA-PG10 - Use only with equipment rated for cylinder pressure.

CGA-PG21 - Open valve slowly.

CGA-PG06 - Close valve after each use and when empty. CGA-PG05 - Use a back flow preventive device in the piping.

CGA-PG11 - Never put cylinders into unventilated areas of passenger vehicles. CGA-PG27 - Read and follow the Safety Data Sheet (SDS) before use.

## 2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

Not applicable

## **SECTION 3: Composition/information on ingredients**

## 3.1. Substance

Not applicable

3.2. Mixture

07/01/2015 EN (English US) SDS ID: PTG-4032 Page 1

## Safety Data Sheet

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Name	Product identifier	%	Classification (GHS-US)
Nitrogen	(CAS No) 7727-37-9	79.1 - 99.999	Compressed gas, H280
Oxygen	(CAS No) 7782-44-7	0.0001 - 20.9	Ox. Gas 1, H270 Compressed gas, H280
Isobutylene	(CAS No) 115-11-7	0.0001 - 1	Liquefied gas, H280
n-Hexane	(CAS No) 110-54-3	0.0001 - 0.9999	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
n-Heptane	(CAS No) 142-82-5	0.0001 - 0.6	Flam. Liq. 2, H225

Full text of H-phrases: see section 16

### **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

First-aid measures after inhalation

Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped. Immediately remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, qualified personnel may give oxygen. Call a physician.

First-aid measures after skin contact

First-aid measures after eye contact

: Adverse effects not expected from this product.

: Immediately flush eyes thoroughly with water for at least 15 minutes. Hold the eyelids open and away from the eyeballs to ensure that all surfaces are flushed thoroughly. Contact an

ophthalmologist immediately.

First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

## 4.2. Most important symptoms and effects, both acute and delayed

No additional information available

### 4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical assistance.

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

Suitable extinguishing media

: Use extinguishing media appropriate for surrounding fire.

### 5.2. Special hazards arising from the substance or mixture

Reactivity

: No reactivity hazard other than the effects described in sub-sections below.

### 5.3. Advice for firefighters

Firefighting instructions

: Evacuate all personnel from the danger area. Use self-contained breathing apparatus (SCBA) and protective clothing. Immediately cool containers with water from maximum distance. Stop flow of gas if safe to do so, while continuing cooling water spray. Remove ignition sources if safe to do so. Remove containers from area of fire if safe to do so. On-site fire brigades must comply with OSHA 29 CFR 1910.156 and applicable standards under 29 CFR 1910 Subpart L—Fire Protection.

Special protective equipment for fire fighters

Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.

## **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

### 6.1.1. For non-emergency personnel

No additional information available

### 6.1.2. For emergency responders

No additional information available

### 6.2. Environmental precautions

Try to stop release. Prevent waste from contaminating the surrounding environment. Prevent soil and water pollution. Dispose of contents/container in accordance with local/regional/national/international regulations. Contact supplier for any special requirements.

### 6.3. Methods and material for containment and cleaning up

No additional information available

### 6.4. Reference to other sections

See also sections 8 and 13.

07/01/2015 EN (English US) SDS ID: PTG-4032 2/11

## Safety Data Sheet

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Precautions for safe handling

: Wear leather safety gloves and safety shoes when handling cylinders. Protect cylinders from physical damage; do not drag, roll, slide or drop. While moving cylinder, always keep in place removable valve cover. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Never insert an object (e.g., wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Slowly open the valve. If the valve is hard to open, discontinue use and contact your supplier. Close the container valve after each use; keep closed even when empty. Never apply flame or localized heat directly to any part of the container. High temperatures may damage the container and could cause the pressure relief device to fail prematurely, venting the container contents. For other precautions in using this product, see section 16.

## 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

Store in a cool, well-ventilated place. Store and use with adequate ventilation. Store only where temperature will not exceed 125°F (52°C). Firmly secure containers upright to keep them from falling or being knocked over. Install valve protection cap, if provided, firmly in place by hand. Store full and empty containers separately. Use a first-in, first-out inventory system to prevent storing full containers for long periods. OTHER PRECAUTIONS FOR HANDLING, STORAGE, AND USE: When handling product under pressure, use piping and equipment adequately designed to withstand the pressures to be encountered. Never work on a pressurized system. Use a back flow preventive device in the piping. Gases can cause rapid suffocation because of oxygen deficiency; store and use with adequate ventilation. If a leak occurs, close the container valve and blow down the system in a safe and environmentally correct manner in compliance with all international, federal/national, state/provincial, and local laws; then repair the leak. Never place a container where it may become part of an electrical circuit.

### 7.3. Specific end use(s)

None.

## SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

PTG-4032	PTG-4032	
ACGIH	Not applicable	
OSHA	Not applicable	
n-Hexane (110-54-3)		
ACGIH	ACGIH TLV-TWA (ppm)	50 ppm
OSHA	OSHA PEL (TWA) (mg/m³)	1800 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	500 ppm
n-Heptane (142-82-5)		
ACGIH	ACGIH TLV-TWA (ppm)	400 ppm
ACGIH	ACGIH TLV-STEL (ppm)	500 ppm
OSHA	OSHA PEL (TWA) (mg/m³)	2000 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	500 ppm
Isobutylene (115-11-7)		
ACGIH	ACGIH TLV-TWA (ppm)	250 ppm
OSHA	Not applicable	
Nitrogen (7727-37-9)		
ACGIH	Not applicable	
OSHA	Not applicable	
Oxygen (7782-44-7)		
ACGIH	Not applicable	
OSHA	Not applicable	

07/01/2015 EN (English US) SDS ID: PTG-4032 3/11

## Safety Data Sheet

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

### 8.2. Exposure controls

Appropriate engineering controls

: Provide adequate general and local exhaust ventilation. Alarm detectors should be used when toxic gases may be released. Product to be handled in a closed system. Ensure exposure is below occupational exposure limits (where available).

Personal protective equipment

: Gloves. Safety glasses.





Eye protection

: Wear safety glasses when handling cylinders; vapor-proof goggles and a face shield during cylinder changeout or whenever contact with product is possible. Select eye protection in accordance with OSHA 29 CFR 1910.133.

Skin and body protection

: Wear metatarsal shoes and work gloves for cylinder handling, and protective clothing where needed. Wear appropriate chemical gloves during cylinder changeout or wherever contact with product is possible. Select per OSHA 29 CFR 1910.132, 1910.136, and 1910.138.

Respiratory protection

When workplace conditions warrant respirator use, follow a respiratory protection program that meets OSHA 29 CFR 1910.134, ANSI Z88.2, or MSHA 30 CFR 72.710 (where applicable). Use an air-supplied or air-purifying cartridge if the action level is exceeded. Ensure that the respirator has the appropriate protection factor for the exposure level. If cartridge type respirators are used, the cartridge must be appropriate for the chemical exposure (e.g., an organic vapor cartridge). For emergencies or instances with unknown exposure levels, use a self-contained breathing apparatus (SCBA).

Thermal hazard protection

: Wear cold insulating gloves when transfilling or breaking transfer connections.

## **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state : Gas
Color : Colorless

Odor No data available No data available Odor threshold рΗ : Not applicable. Melting point No data available Freezing point No data available Boiling point No data available Flash point No data available Relative evaporation rate (butyl acetate=1) : No data available Relative evaporation rate (ether=1) : Not applicable. Flammability (solid, gas) No data available **Explosion limits** : No data available Explosive properties : Not applicable.

Oxidizing properties : None.

Vapor pressure : Not applicable.

Relative density : No data available

Relative vapor density at 20 °C : No data available

Solubility : Water: No data available

Log Pow : Not applicable.

Log Kow : Not applicable.

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity : No data available

Viscosity, kinematic : Not applicable.

Viscosity, dynamic : Not applicable.

### 9.2. Other information

No additional information available

07/01/2015 EN (English US) SDS ID: PTG-4032 4/11

## Safety Data Sheet

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

## SECTION 10: Stability and reactivity

## 10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No additional information available

### 10.4. Conditions to avoid

No additional information available

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

No additional information available

## **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

n-Hexane (110-54-3)	
LD50 dermal rabbit	3000 mg/kg
LC50 inhalation rat (ppm)	48000 ppm/4h
ATE US (dermal)	3000.000 mg/kg body weight
ATE US (gases)	48000.000 ppmV/4h
n-Heptane (142-82-5)	
LD50 dermal rabbit	3000 mg/kg
LC50 inhalation rat (mg/l)	103 g/m³ (Exposure time: 4 h)
LC50 inhalation rat (ppm)	50266 ppm/1h
ATE US (dermal)	3000.000 mg/kg body weight
ATE US (gases)	25133.000 ppmV/4h
ATE US (vapors)	103.000 mg/l/4h
ATE US (dust, mist)	103.000 mg/l/4h
Isobutylene (115-11-7)	
LC50 inhalation rat (mg/l)	620 mg/l/4h
LC50 inhalation rat (ppm)	≥ 10000
ATE US (gases)	10000.000 ppmV/4h
ATE US (vapors)	620.000 mg/l/4h
ATE US (dust, mist)	620.000 mg/l/4h

Skin corrosion/irritation : Not classified

pH: Not applicable.

Serious eye damage/irritation : Not classified

pH: Not applicable.

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified

## Isobutylene (115-11-7)

National Toxicology Program (NTP) Status 1 - Evidence of Carcinogenicity

Reproductive toxicity : Not classified Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated

exposure)

: Not classified

07/01/2015 EN (English US) SDS ID: PTG-4032 5/11

Safety Data Sheet according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Aspiration hazard : Not classified

Aspiration nazard	. Not classified
SECTION 12: Ecological informa	tion
12.1. Toxicity	
Ecology - general	: HARMFUL TO AQUATIC LIFE WITH LONG LASTING EFFECTS.
n-Hexane (110-54-3)	
LC50 fish 1	2.54 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
n-Heptane (142-82-5)	
LC50 fish 1	375.0 mg/l (Exposure time: 96 h - Species: Cichlid fish)
12.2. Persistence and degradability	
PTG-4032	
Persistence and degradability	No ecological damage caused by this product.
Isobutylene (115-11-7)	
Persistence and degradability	The substance is biodegradable. Unlikely to persist.
Nitrogen (7727-37-9)	
Persistence and degradability	No ecological damage caused by this product.
Oxygen (7782-44-7)	
Persistence and degradability	No ecological damage caused by this product.
12.3. Bioaccumulative potential	
PTG-4032	
Log Pow	Not applicable.
Log Kow	Not applicable.
Bioaccumulative potential	No ecological damage caused by this product.
n-Heptane (142-82-5)	
Log Pow	4.66
Isobutylene (115-11-7)	
Log Pow	2.35
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.
Nitrogen (7727-37-9)	
Log Pow	Not applicable.
Log Kow	Not applicable.
Bioaccumulative potential	No ecological damage caused by this product.
Oxygen (7782-44-7)	N. C. P. D.
Log Pow	Not applicable.  Not applicable.
Log Kow Bioaccumulative potential	No ecological damage caused by this product.
	110 coological damage caused by this product.
12.4. Mobility in soil	
PTG-4032	No data available
Mobility in soil	No data available.
Isobutylene (115-11-7)	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.
Nitrogen (7727-37-9)	
Mobility in soil	No data available.
Ecology - soil	No ecological damage caused by this product.
Oxygen (7782-44-7)	
Mobility in soil	No data available.
Ecology - soil	No ecological damage caused by this product.

07/01/2015 EN (English US) SDS ID: PTG-4032 6/11

## Safety Data Sheet

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

12.5. Other adverse effects

Effect on ozone layer : None.

Effect on the global warming : No known ecological damage caused by this product.

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Waste disposal recommendations : Do not attempt to dispose of residual or unused quantities. Return container to supplier.

## **SECTION 14: Transport information**

### **Department of Transportation (DOT)**

In accordance with DOT

Transport document description : UN1956 Compressed gas, n.o.s., 2.2

UN-No.(DOT) : UN1956

Proper Shipping Name (DOT) : Compressed gas, n.o.s.

Transport hazard class(es) (DOT) : 2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115

Hazard labels (DOT) : 2.2 - Non-flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx) : 302;305
DOT Packaging Bulk (49 CFR 173.xxx) : 314;315

DOT Symbols : G - Identifies proper shipping name (PSN) requiring the addition of technical name(s) in

parentheses following the PSN.

DOT Packaging Exceptions (49 CFR 173.xxx) : 306;307
DOT Quantity Limitations Passenger aircraft/rail : 75 kg

(49 CFR 172.101 HMT, Column 9a)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 172.101 HMT, Column 9b)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

### **Additional information**

Other information : No supplementary information available.

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's

compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers:
- Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure cylinder valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided)

is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.

**ADR** 

Transport document description : UN 1956 COMPRESSED GAS, N.O.S. (Nitrogen, n-Hexane), 2.2, (E)

Class (ADR) : 2 - Gases
Hazard identification number (Kemler No.) : 20
Classification code (ADR) : 1A

Hazard Class Labels (ADR) : 2.2 - Non-flammable compressed gas

2

07/01/2015 EN (English US) SDS ID: PTG-4032 7/11

## Safety Data Sheet

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Orange plates :

20 1956

Tunnel restriction code (ADR) : E
Limited quantities (ADR) : 120ml
Excepted quantities (ADR) : E1

Transport by sea

UN-No. (IMDG) : 1956

Proper Shipping Name (IMDG) : COMPRESSED GAS, N.O.S.

Class (IMDG) : 2.2 - Non-flammable, non-toxic gases

 Limited quantities (IMDG)
 : 120ml

 EmS-No. (1)
 : F-C

 MFAG-No
 : 620

 EmS-No. (2)
 : S-V

Air transport

UN-No. (IATA) : 1956

Proper Shipping Name (IATA) : COMPRESSED GAS, N.O.S.

Class (IATA) : 2
Instruction "cargo" (ICAO) : 200
Instruction "passenger" (ICAO) : 200

Instruction "passenger" - Limited quantities : FORBIDDEN

(ICAO)

## **SECTION 15: Regulatory information**

## 15.1. US Federal regulations

n-Hexane (110-54-3)	
Listed on the United States TSCA (Toxic Substan Subject to reporting requirements of United States	
SARA Section 313 - Emission Reporting	1.0 %

## n-Heptane (142-82-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.

## Isobutylene (115-11-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

## Nitrogen (7727-37-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

## Oxygen (7782-44-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

## 15.2. International regulations

## **CANADA**

n-Hexane (110-54-3)			
Listed on the Canadian DSL (Domestic Substanc	the Canadian DSL (Domestic Substances List)		
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects		
n-Heptane (142-82-5)			
isted on the Canadian DSL (Domestic Substances List)			
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects		
Isobutylene (115-11-7)			
Listed on the Canadian DSL (Domestic Substances List)			

07/01/2015 EN (English US) SDS ID: PTG-4032 8/11

## Safety Data Sheet

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Nitrogen (7727-37-9)	rogen (7727-37-9) ted on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian DSL (Domestic		
WHMIS Classification	Class A - Compressed Gas	
Oxygen (7782-44-7)		
Listed on the Canadian DSL (Domestic Substances List)		
WHMIS Classification	Class A - Compressed Gas Class C - Oxidizing Material	

### **EU-Regulations**

### n-Hexane (110-54-3)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

### n-Heptane (142-82-5)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

### Isobutylene (115-11-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

### Nitrogen (7727-37-9)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

### Oxygen (7782-44-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Gas 1 H220 Compressed gas H280 Aquatic Chronic 3 H412

Full text of H-phrases: see section 16

### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

No additional information available

## **National regulations**

## n-Hexane (110-54-3)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Japanese Pollutant Release and Transfer Register Law (PRTR Law)

Listed on the Canadian IDL (Ingredient Disclosure List)

## n-Heptane (142-82-5)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the Canadian IDL (Ingredient Disclosure List)

## Isobutylene (115-11-7)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

## Nitrogen (7727-37-9)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

07/01/2015 EN (English US) SDS ID: PTG-4032 9/11

## Safety Data Sheet

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

### Oxygen (7782-44-7)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

### 15.3. US State regulations

### n-Hexane (110-54-3)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

### n-Heptane (142-82-5)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

## Isobutylene (115-11-7)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

## Nitrogen (7727-37-9)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

## Oxygen (7782-44-7)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

### **SECTION 16: Other information**

Revision date

Training advice

Other information

: 07/01/2015

: Users of breathing apparatus must be trained.

When you mix two or more chemicals, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an industrial hygienist or other trained person when you evaluate the end product. Before using any plastics, confirm their compatibility with this product. Praxair asks users of this product to study this SDS and become aware of the product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this SDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information. The opinions expressed herein are those of qualified experts within Praxair, Inc. We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and the conditions of use are not within the control of Praxair, Inc., it is the user's obligation to determine the conditions of safe use of the product. Praxair SDSs are furnished on sale or delivery by Praxair or the independent distributors and suppliers who package and sell our products. To obtain current SDSs for these products, contact your Praxair sales representative, local distributor, or supplier, or download from www.praxair.com. If you have questions regarding Praxair SDSs, would like the document number and date of the latest SDS, or would like the names of the Praxair suppliers in your area, phone or write the Praxair Call Center (Phone: 1-800-PRAXAIR/1-800-772-9247; Address: Praxair Call Center, Praxair, Inc., P.O. Box 44, Tonawanda, NY 14151-0044). PRAXAIR and the Flowing Airstream design are trademarks or registered trademarks of Praxair Technology, Inc. in the United States and/or other countries.

07/01/2015 EN (English US) SDS ID: PTG-4032 10/11

# Safety Data Sheet

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

## Full text of H-phrases:

kt of Fr-piliases.	
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Asp. Tox. 1	Aspiration hazard Category 1
Compressed gas	Gases under pressure Compressed gas
Flam. Liq. 2	Flammable liquids Category 2
Liquefied gas	Gases under pressure Liquefied gas
Ox. Gas 1	Oxidizing gases Category 1
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	HIGHLY FLAMMABLE LIQUID AND VAPOR
H270	MAY CAUSE OR INTENSIFY FIRE; OXIDIZER
H280	CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED
H304	MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS
H315	CAUSES SKIN IRRITATION
H336	MAY CAUSE DROWSINESS OR DIZZINESS
H373	MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED
	OR REPEATED EXPOSURE
H401	TOXIC TO AQUATIC LIFE
H411	TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

07/01/2015 EN (English US) SDS ID: PTG-4032 11/11